

AMERICAN WRITING INK. -- VV-L-820;LUBRICATING OIL -- 9150-00-231-9045

=====
Product Identification
=====

Product ID:VV-L-820;LUBRICATING OIL
MSDS Date:01/01/1987
FSC:9150
NIIN:00-231-9045
MSDS Number: BDLDN
=== Responsible Party ===
Company Name:AMERICAN WRITING INK.
Address:35 FARNSWORTH STREET
City:BOSTON
State:MA
ZIP:02210-1210
Country:US
Info Phone Num:617-482-9167
Emergency Phone Num:617-482-9167
CAGE:82956

=== Contractor Identification ===
Company Name:AMERICAN INK AND OIL CORP
Address:33 ENDICOTT STREET
Box:City:NORWOOD
State:MA
ZIP:02062-3006
Country:US
Phone:781-762-0026 / FAX: 781-762-1617
CAGE:82956

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM BASE OIL (COMPLEX MIXTURE OF PETROLEUM HYDROCARBON).
Other REC Limits:5 MG/CUM (OIL MIST)

=====
Hazards Identification
=====

Routes of Entry: Inhala

tion:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE: MILE SKIN IRRITATION OR EYES;
OIL MIST MAY IRRITATE RESPIRATORY TRACT. CHRONIC: NO DATA
AVAILABLE.

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE
MILD SKIN IRRITATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.

=====
===== First Aid Measures =====

First Aid:IN CASE OF SKIN CONTACT,WASH THOROUGHLY WITH SOAP AND WARM
WATER.IF SPLASHED INTO THE EYES,FLUSH WITH CLEAR WATER FOR 15
MINUTES OR UNTIL. IRRITATION SUBSIDES.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:320F,160C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY
CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS
LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN

=====
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID.ADD ABSORBENT
(SAND,EARTH,SAWDUST,ETC)KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND
WATERCOURCES BY DIKING OR IMPOUNDING.INFORM LOCAL AUTHORITIES IF
NEEDED.

=====
===== Handling and Storage =====

Han

dling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.DO NOT HANDLE OR STORE NEAR HEAT,SPARKS,FLAMES OR STRONG OXIDANTS.

Other Precautions:AVOID BREATHING OIL MIST.REMOVE OIL SOAKED CLOTHING AND LAUNDER PRIOR TO REUSE.DISCARD OIL SOAKED SHOES.WASH SKIN THOUROUGHLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOS TLV,NIOSH/MESA APPR SELF-CNTND BRTHG APP (POS PR MODE)

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION

Supplemental Safety and Health

MSDS IS UNDATED.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:540F/282C

Vapor Pres: