

OCTAGON PROCESS INC. -- VV-L-800C LUBRICATING OIL -- 9150-00-231-9062

=====
Product Identification
=====

Product ID:VV-L-800C LUBRICATING OIL

MSDS Date:06/28/1993

FSC:9150

NIIN:00-231-9062

MSDS Number: BDLFB

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-313-1187

Emergency Phone Num:201-945-94

00

Preparer's Name:J.J. BURGARD

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (MIST)

ACGIH TLV:5 MG/M3 (MIST) 9293

Ingred Name:OTHER COMPONENTS (NOT SPECIFIED)

Other REC Limits:NONE SPECIFIED

=====

==== Hazards Identification =====

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE MILD EYE IRRITATION. MILD TO MODERATE SKIN IRRITATION WITH PROLONGED OR REPEATED CONTACT. PRACTICALLY NON-TOXIC BY INGESTION. MAY CAUSE SLIGHT IRRITATION TO THE GASTROINTESTINAL TRACT.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS

CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:MILD EYE IRRITATION/REDNESS, MILD TO MODERATE SKIN IRRITATION, RESPIRATORY TRACT IRRITATION FROM INHALING MIST, GASTROINTESTINAL DISTURBANCES.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

==== First Aid Measures =====

First Aid:EYES: FLOOD WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

SKIN: WASH WITH WATER AND MILD

SOAP. INHALATION: NONE NORMALLY REQUIRED. INGESTION: GIVE LIQUIDS AND INDUCE VOMITING UNLESS VICTIM IS UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

==== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:320F,160C

Lower Limits:1.0%

Upper Limits:7.0%

Extinguishing Media:WATER FOG, CHEMICAL FOAM, DRY CHEMICAL OR CARBON DIOXIDE

Fire Fighting Procedures:KEEP FIRE-EXPOSED CONTAINERS COOL WITH WATER

FOG. DO NOT USE DIRECT WATER STREAM.

Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

==== Accidental Release Measures =====

Spill Release Procedures:DIKE AND CONTAIN SPILL. DO NOT ALLOW MATERIAL TO ENTER DRAINS, SEWERS OR WATERWAYS. RECOVER FREE LIQUID IF POSSIBLE. ABSORB REMAINING PRODUCT WITH INERT MATERIAL AND PLACE INTO PROPER CONTAINERS FOR DISPOSAL. COMPLY WITH ALL SPILL NOTIFICATIONS.

Neutralize

ng Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:ALL USERS SHOULD CONSULT MSDS BEFORE HANDLING MATERIAL. STORE IN A COOL, DRY PLACE. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:WASH HANDS AND FACE AFTER HANDLING MATERIAL. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. DISPOSE OF OIL SOAKED FOOTWARE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKING IN A CONFINED AREA OR MISTING IS OCCURRING, USE NIOSH-APPROVED RESPIRATORY PROTECTION (REFER TO 29CFR 1910.134)

Ventilation:USE FORCED VENTILATION TO MINIMIZE VAPOR CONCENTRATIONS.

Protective Gloves:RUBBER OR NEOPRENE

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:PROVIDE LOCAL EMERGENCY SHOWERS AND EYE WASH STATIONS.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health
CLEAN CONTAMINATED EQUIPMENT BEFORE STARTING ANY REPAIR WORK. USE THIS PRODUCT ONLY AS DIRECTED. SEE MANUFACTURER'S DIRECTIONS.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:550F,288C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:< 0.01

Vapor Density:NOT GIVEN

Spec Gravity:0.89

Evaporation Rate & Reference: