

AMERON PROTECTIVE COATINGS -- 703-200 -- 8010-00-234-5176

=====  
Product Identification  
=====

Product ID:703-200

MSDS Date:01/01/1987

FSC:8010

NIIN:00-234-5176

MSDS Number: BDLKD

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

City:BREA

State:CA

ZIP:92622-1020

Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4

=== Cont

actor Identification ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Other REC Limits:STEL 400 PPM

OSHA PEL:100 PPM

ACGIH TLV:300 PPM

=====  
Hazards Identification  
=====

Routes of Entry:

Inhalation: YES Skin: NO Ingestion: NO  
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO  
Health Hazards Acute and Chronic: INHALATION: ANESTHETIC. IRRITATION OF  
RESPIRATORY TRACT. MAY CAUSE NERVOUS SYSTEM DEPRESSION. SKIN/EYES:  
IRRITATION.  
Effects of Overexposure: IRRITATION

=====  
===== First Aid Measures =====

First Aid: SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
===== Fire Fighting Measures =====

Flash Point Method: TCC  
Flash Point: 100F  
Lower Limits: 1.1  
Extinguishing Media: SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM  
Fire Fighting Procedures: USE SELF CONTAINED BREATHING APPARATUS FOR  
FIREMEN.  
Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: DON'T STORE ABOVE 120F. STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE  
FLAMMABLES.  
Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID  
FREE FALL OF LIQUID IN EXCESS OF FEW INCHES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR/AIR

SUPPLIED

RESPIRATOR. RESPIRATOR USED BASED ON CHEMICAL CONDITION & CONDITIONS OF USE.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST AS NECESSARY.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:270-390F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:54

===== Sta  
bility and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRE, HEAT, HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.