

NONFLUID OIL CORP. -- VV-G-671 (GREASE,GRAPHITE) -- 9150-00-235-5568

=====
Product Identification
=====

Product ID:VV-G-671 (GREASE,GRAPHITE)

MSDS Date:12/01/1986

FSC:9150

NIIN:00-235-5568

MSDS Number: BDLPM

=== Responsible Party ===

Company Name:NONFLUID OIL CORP.

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105

Country:US

Info Phone Num:(201)344-3451

Emergency Phone Num:(201)344-3451

CAGE:7

6736

=== Contractor Identification ===

Company Name:NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS COMPONENTS (PER MSDS)SEE INGREDIENTS #2,3 AND
4 AS GIVEN IN CTDF

Other REC Limits:5MG/CUM AS OIL MIST

Ingred Name:CALCIUM SOAP (USED AS THICKENER)

Ingred Name:GRAPHITE, NATURAL

CAS:7

782-42-5
RTECS #:MD9659600
OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

Ingrid Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')
CAS:8012-95-1
RTECS #:PY8030000
Other REC Limits:5MG/CUM AS OILMIST
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:AS WITH ALL PETROLEUM
PRODUCTS,PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD
IRRITATION. DEFATTING ON SKIN IS POSSIBLE. EXPOSUR
E TO FUMES OR
MISTS MAY CAUSE MUCOUS MEMBRANE IRRITATION.
Effects of Overexposure:MILD IRRITATION OF SKIN AND MUCOUS MEMBRANE.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH LARGE AMOUNTS OF WATER AND SEE A
DOCTOR;SKIN:WIPE OFF AND WASH WITH SOAP AND WATER;INHALATION:REMOVE
TO FRESH AIR;INGESTION:GIVE WATER & SEEK MEDICAL AID.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:410F
,210C
Lower Limits:1
Upper Limits:6
Extinguishing Media:CO*2,DRY CHEMICAL,FOAM AND WATER FOG (CAREFULLY TO
PREVENT FROTHING)
Fire Fighting Procedures:WEAR SCBA WITH FACE SHIELD IN ENCLOSED AREAS.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. ELIMINATE IGNITION SOURCES. RECOVER
FREE PRODUCT. ADD ABSORBENT MATERIAL SUCH AS CLAY TO SPILL AREA.
SWEEP OR SCRAPE UP.

=====
===== Handli

ng and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. HANDLE AND STORE AS PETROLEUM PRODUCTS. DO NOT STORE OR MIX WITH OXIDIZING MATERIALS. AVOID EXCESSIVE HEAT OR FLAMES.

Other Precautions:AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH EYES & INHALATION OF FUMES,VAPORS OR MISTS. DO NOT INGEST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIRED. RECOMMENDED IF FUMING OR MISTING.

Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL) RECOMMENDED.

Protective Gloves:GLOVES RECOMMENDED FOR REPEATED CONTACT.

Eye Protection:GOGGLES RECOMMENDED IF SPLASHING OR MIST

Other Protective Equipment:NORMALLY NOT REQUIRED. PROTECTIVE CLOTH RECOMMENDED IF FUMING OR MISTING.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. DO NOT WEAR CONTAMINATED CLOTHING. REMOVE AND LAUNDER BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties

=====

HCC:V6

Vapor Pres:0.01

Vapor Density:11

Spec Gravity:0.92

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK SEMI-SOLID PASTE. SLIGHT PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXCESSIVE HEAT & OPEN FLAMES.

Hazardous Decomposition Products:CO,CO*2

===== Disposal Consider

ations =====

Waste Disposal Methods:DISPOSE OF IAW FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.