

DAVIS-HOWLAND OIL CORPORATION -- VV-L-1071A;LUBRICATING OIL -- 9150-00-240-2260  
===== Product Identification =====

Product ID:VV-L-1071A;LUBRICATING OIL

MSDS Date:01/01/1987

FSC:9150

NIIN:00-240-2260

MSDS Number: BDMGV

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6650

Emergency

Phone Num:716-473-6650

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:COMPLEX MIXTURE OF HYDROCARBONS

Fraction by Wt: 100.0%

Other REC Limits:5M

# G/CUM FOR OIL MIST

## ===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES  
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF  
EYES,SKIN,RESPIRATORY TRACT OR G.I. TRACT. CHRONIC:SKIN IRRITATION  
OR DERMATITIS.  
Effects of Overexposure:IRRITATION OF SKIN,EYES,RESPIRATORY OR G.I.  
TRACT.PROLONGED CONTACT MAY CAUSE IRRITATION OR DERMATITIS.  
Medical Cond Aggravated by Exposure:NOT KNOWN

## ===== First Aid Measures =====

First Aid:IN CASE OF SKIN CONTACT,WASH WITH SOAP AND WATER.IF SPLASHED  
INTO EYES,FLUSH WITH CLEAR WATER UNTIL IRRITATION  
SUBSIDES.INHALATION:REMOVE TO FRESH AIR,CALL A PHYSICIAN IF NEEDED.

## ===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:560F/293C  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:FOAM,DRY CHEMICAL,CO\*2,WATER SPRAY OR FOG.COOL  
EXPOSED CONTAINERS WITH WATER.  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED  
AREA.  
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

## ===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION.RECOVER FREE  
LIQUID.ADD ABSORBENT TO SPILL AREA,RECOVER FOR PROPER DISPOSAL.

## ===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED  
AREA.

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/OIL MIST IF ABOVE TLV OR PEL.

Ventilation: ADEQUATE VENTILATION

Protective Gloves: IMPERVIOUS

Eye Protection: GOGGLES OR SAFETY GLASSES

Other Protective Equipment: FULL PROTECTION FOR SKIN (FOOT WEARS), APRONS

Work Hygienic Practices: AVOID CONTACT WITH EYES AND SKIN. DO NOT BREATHE VAPORS. WASH THOROUGHLY AFTER EACH USE; DO NOT USE CONTAMINATED CLOTHES.

Supplemental Safety and Health

MSDS RECEIVED BY DGSC: 9 OCT 1987.

=====  
===== Physical/Chemical Properties =====

HCC: V6

Boiling Pt: B.P. Text: 698/370C

Vapor Pres: 20

Solubility in Water: NEGLIGIBLE

Appearance and Odor: DARK GREEN COLOR, MILD PETROLEUM ODOR

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDANTS LIKE LIQUID CHLORINE AND CONC O\*2.

Stability

Condition to Avoid: EXTREME HEAT

Hazardous Decomposition Products: CO GAS IN THE CASE OF INCOMPLETE COMBUSTION.

=====  
===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE OR DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in

no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.