View NSN Online: https://aerobasegroup.com/nsn/6810-00-242-3645

UNION CARBIDE CORP., SOLVENT & COATING DIV. -- ETHYL ALCOHOL, 200 PROOF

6810-00-242-3645

Product ID:ETHYL ALCOHOL,200 PROOF

MSDS Date:04/01/1985

FSC:6810

NIIN:00-242-3645

MSDS Number: BDMSQ === Responsible Party ===

Company Name: UNION CARBIDE CORP., SOLVENT & COATING DIV.

Address:OLD RIDGEBURY RD

City:DANBURY

State:CT ZIP:06817

Info Phone Num:304-744-3487

Emerge

ncy Phone Num:304-744-3487 OR 800-822-4357

CAGE:61637

=== Contractor Identification ===

Company Name: DECAL CHEMICAL CORP

Address:333 RT 9W

Box:131

City: CONGERS

State:NY ZIP:10920 Country:US

Phone:914-268-9258

CAGE:7L402

Company Name: UNION CARBIDE CORP Address: 39 OLD RIDGEBURY ROAD

Box:City:DANBURY

State:CT

ZIP:06817-0001 Country:US

Phone:800-822-4357/732-563-5522 (MSDS)

CAGE:61637

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL ALCOHOL (ETHANOL)

CAS:64-17

RTECS #:KQ6300000 Fraction by Wt: 100% OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT CAUSES CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS NARCOSIS. PRODUCT CONTAINS A DENATURANT (POISON) TO MAKE IT UNSUITABLE FOR BEVERAGE PURPOSES. EFFECTS OF THE DENATURANT VARY DEPENDING U

PON THE ON E USED.

Effects of Overexposure:EYE,SKIN CONTACT:MILD IRRITATION INHALED/INGESTED:WEAKNESS,DROWINESS,VOMITING,DRUNKNESS,POSSIBLE BLURRED VISION,LND BLINDNESS.

Medical Cond Aggravated by Exposure: NONE REPORTED

First Aid:EYE:FLUSH WITH WATER 15MIN. SKIN:REMOVE CONTAMINATED CLOTHING. WASH AREA WITH SOAP AND WATER. LAUNDER CLOTHING BEFORE REUSE.INHALED:REMOVE FROM EXPOSURE. GIVE ARTIFICIAL RESPIRATION O R

OXYGEN IF NEEDE D. INGESTED:DO NOT INDUCE VOMITING. GIVEWATER OR MILK. (NOTHING BY MOUTH IF UNCONSCIOUS) GET IMMEDIATE MEDICAL CARE.IF SYMPTOMS PERSIST OR ARE SEVERE,GET MEDICAL CARE.

============ Fire Fighting Measures =========================

Flash Point Method:TCC Flash Point:55F/13C

Autoignition Temp: Autoignition Temp Text: 793F

Lower Limits:4.3 Upper Limits:19

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG.

Fire Fighting Procedures:WEAR SELF CONTAINED

BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE

======== Accidental Release Measures ==========


Spill Release Procedures:REMOVE IGNITION SOURCES & VENTILATE AREA. RECOVER AS LIQUID. ABSORB WITH SAWDUST,ETC. SMALL QUANTITIES MAY BE WIPED UP WITH CLOTH,PAPER.

Neutralizing Agent:NONE

=========== Handling and Storage ================

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL VENTILATED AREA,AWAY FROM IGNITION SOURCES.

Othe



========

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL,REGULATIONS. HMIS SUGGEST INCINERATE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.