View NSN Online: https://aerobasegroup.com/nsn/6810-00-242-3645 DECAL CHEMICAL CORP. -- ETHANOL,200 PROOF -- 6810-00-242-3645 ============ Product Identification =============== Product ID:ETHANOL,200 PROOF MSDS Date:01/01/1985 FSC:6810 NIIN:00-242-3645 MSDS Number: BDMSS === Responsible Party === Company Name: DECAL CHEMICAL CORP. Address:333 RT 9W Box:131 City: CONGERS State:NY ZIP:10920 Country:US Emergency Phone Num:914-268-9258 CAGE:7L402 === Contractor Identification === Company Name: DECAL CHEMICAL CORP Address:333 RT 9W Box:131 City: CONGERS State:NY ZIP:10920 Country:US Phone:914-268-9258 CAGE:7L402 ======= Composition/Information on Ingredients ======== Ingred Name: ETHYL ALCOHOL (ETHANOL) CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 100% OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

============ Hazards Identification =========================

Effects of Overexposure: SWALLOWING: INEBRIATION, HDACHE, NAUSEA, VOMIT. LIQ IRRIT EYES. BRTH

NG VAPORS: DROWSINESS.
======================================
First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN, EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS C LEAR, NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.
======================================
Flash Point:58F,14C,TCC Lower Limits:3.3 Upper Limits:19.0 Ex
tinguishing Media:CARBON DIOXIDE, DRY CHEM, SM FIRES. ALCOHOL FOAM, LG FIRES.
Fire Fighting Procedures:WEAR SCBA,COOL CANS W/WATER.WATER FOG WILL
REDUCE BURN RATE. Unusual Fire/Explosion Hazard:DANGEROUS FIRE HAZARD,MODERATE EXPLOSION HAZARD.
========= Accidental Release Measures ==========
Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SM SPILLS SHOULD BE FLUSHED W/LG QTY OF WATER. LG SPILLS SHOULD BE COLLECTED FOR DISPOSAL.
===== Handling and Storage ====================================
Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. KEEP CNTNR CLOSED. USE W/ADEQUATE VENT. Other Precautions:STORE IN COOL,DRY WELL VENTILATED,FIRE RESISTANT AREAS AWAY FROM OXIDIZERS & SOURCES OF IGNITION.ELECTRICALLY BOND & GROUND METAL CONTAINERS.STORE OUT OF DIRECT SUNLIGHT.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:AIR-SUPP MASK FOR HI CONC Ventilation:LOC

Eye Protection:GOGGLES Other Protective Equipment:PROTECTIVE CLOTHING TO MINIMIZE CONTACT,EYEWASH,SFTY SHOWER
Supplemental Safety and Health
======================================
HCC:F2 Boiling Pt:B.P. Text:172.9F, 78C Vapor Pres:44 Vapor Density:1.6 Spec Gravity:0.7905
Evaporation Rate & Evaporation R
Percent Volatiles by Volume:100
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZERS
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE
======= Disposal Considerations ===========
Waste Disposal Methods:PLACE COLLECTED MATL IN CNTNR SUITABLE FO

AL PREFERABLE, GEN ACCEPTABLE

Protective Gloves:PLASTIC

Waste Disposal Methods:PLACE COLLECTED MATL IN CNTNR SUITABLE FOR SHIPMENT TO DISPOSAL AREA. DISPOSAL CAN BE ACCOMPLISHED BY INCINERATION IN FURNA
CE WHERE PERMITTED BY FED, STATE, LOCAL REG.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of

