

ASHLAND OIL INC. -- TECTYL 894 -- 8030-00-244-1293

=====
Product Identification
=====

Product ID:TECTYL 894
MSDS Date:01/01/1985
FSC:8030
NIIN:00-244-1293
MSDS Number: BDMZW
=== Responsible Party ===
Company Name:ASHLAND OIL INC.
Address:1409 WINCHESTER AVE
Box:391
City:ASHLAND
State:KY
ZIP:41114
Country:US
CAGE:81355

==== Contractor Identification ====

Company Name:ASHLAND INC
Address:1409 WINCHES
TER AVE
Box:391
City:ASHLAND
State:KY
ZIP:41114
Country:US
Phone:800-622-6846
CAGE:81355

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS
Fraction by Wt: 40%
ACGIH TLV:500 PPM

Ingred Name:PETROLEUM OIL *FOR OIL MIST
Fraction by Wt: 20%
ACGIH TLV:5MG/CUM*

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE IRRIT;EXCESSIVE INHALATION MAY CAUSE
DIZZINESS, NAUSEA.

=====
First Aid
=====

Measures =====

First Aid:FLAUSH EYES W/WATER,FLUSH SKIN W/SOAP & WATER. IF SWALLOWED,DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:105F CC 41C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:CO*2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCE,STOP SPILL AT SOURCE,CONTAIN SPILL BY DIKE,ETC., PUMP INTO SALVAGE TANK

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT W/EYES & PROLONGED CONTACT W/SKIN. AVOID BREATHING VAPOR. WASH AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQD
Ventilation:LOC EXHAUST.SPEC VENT AS REQD TO MAINTN LEVLS BELOW EST TLV.
Protective Gloves:LONG GLOVES
Eye Protection:SAFETY GLASSES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:310F 154C
Vapor Pres:UNK
Vapor Density:>1
Spec Gravity: