

PENRECO -- PETROTECT 2,MIL-C-16173,GRADE 2 -- 8030-00-244-1295

=====  
Product Identification  
=====

Product ID:PETROTECT 2,MIL-C-16173,GRADE 2

MSDS Date:01/01/1985

FSC:8030

NIIN:00-244-1295

MSDS Number: BDNBF

=== Responsible Party ===

Company Name:PENRECO

Address:700 MILIAM ST PENNZOIL PL

Box:2967

City:HOUSTON

State:TX

ZIP:77252

Country:US

CAGE:PENRE

=== Contractor Identification ===

Company Name:P

ENRECO

Address:4401 PARK AVENUE

City:DICKINSON

State:TX

ZIP:77539

Country:US

Phone:713-236-6070

CAGE:PENRE

Company Name:PENRECO, DIV OF PENNZOIL CO

Address:700 MILIAM ST

Box:2967

City:HOUSTON

State:TX

ZIP:77252

Country:US

Phone:800-245-3952

CAGE:86459

=====  
Composition/Information on Ingredients  
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 36%

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

=====  
Hazards Identification  
=====

=====

Effects of Overexposure:EYE: BURN/IRRIT. SKIN: DEFATTING. VAPORS:  
IRRIT,DIZZINESS,DROWSINESS,PNEUMONIA,COMA. INGEST: GI IRRIT

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN. SKIN: WASH WITH  
SOAP & WATER,REMOVE CONTAMINATED CLOTHES. INHALATION: REMOVE TO  
FRESH AIR,GIVE ARTIF RESP IF NEEDED,CALL MD. INGESTION: DO NOT  
INDUCE VOMIT ING,CALL A DOCTOR IMMEDIATELY.

===== Fire F  
ighting Measures =====

Flash Point:100F/37C (ASTM)  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE  
Fire Fighting Procedures:TREAT AS OIL FIRE,WATER ONLY TO COOL EXPOSED  
CONTAINERS  
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN  
BURNING.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP MATERIAL INTO WASTE CONTAINERS,OR  
ABSORB WITH DRY SAND OR OIL ABSORBENTS.  
CLEAN SPILL AREA WITH  
DETERGENT SOLUTIONS OR SAFETY SOLVENTS. PROVIDE ADEQUATE  
VENTILATION DURING CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM  
HEAT,OPEN FLAME,AND OXIDIZING MATERIALS.  
Other Precautions:FIRE EXTINGUISHERS MUST BE KEPT READILY AVAILABLE &  
PERSONNEL TRAINED IN PROPER USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protectio

n:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN

Ventilation:LOCAL/GENERAL

Protective Gloves:RUBBER SYNTH

Eye Protection:SPLASH PROOF GOGGLES

Other Protective Equipment:SYNTHETIC RUBBER PROTECTIVE  
CLOTHING,BOOTS,APRON.

Supplemental Safety and Health

THE 50% DISTILLATION TEMPERATURE RANGES BETWEEN 330 TO 340F,TYPICALLY.

PKG: 55 GAL DRUM SOLVENT CONTAINS NO DETECTABLE BENZENE (IE: