

EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV -- ETHYL ACETATE -- 6810-00-245-6695
===== Product Identification =====

Product ID:ETHYL ACETATE

MSDS Date:10/03/1996

FSC:6810

NIIN:00-245-6695

MSDS Number: BDNFW

=== Responsible Party ===

Company Name:EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV

Address:EASTMAN RD

Box:511

City:KINGSPORT

State:TN

ZIP:37662

Country:US

Info Phone Num:423-229-2000

Emergency Phon

e Num:HEALTH 800-EASTMAN; 800-424-9300

CAGE:7B604

=== Contractor Identification ===

Company Name:AMJAY CORP. DBA AMJAY CHEMICALS

Address:11200 WESTHEIMER SUITE 310

Box:218786

City:HOUSTON

State:TX

ZIP:77218-8786

Country:US

Phone:713-492-2000

CAGE:64184

Company Name:EASTMAN KODAK CO TENNESSEE EASTMAN CO DIV

Address:EASTMAN RD

Box:511

City:KINGSPORT

State:TN

ZIP:37662

Country:US

Phone:615-229-2000

CAGE:7B604

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL A

CETATE (SARA III)
CAS:141-78-6
RTECS #:AH5425000
Fraction by Wt: 85%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:EYES-IRRITATION,SKIN-PROLONGED CONTACT DRIES &
CRACKS.VAPOR IRRITATES MUCOUS MEMBRANES,NARCOTIC EFF.

=====
First Aid Measures
=====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES.CALL DOCTOR.SKIN-FLUSH
WI
TH WATER.INHALATION-REMOVE TO FRESH AIR

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:24.8F,-4.0C
Lower Limits:2.02
Upper Limits:10.7
Extinguishing Media:WATER SPRAY,CARBON DIOXIDE,DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTAIN SPILL,IF SMALL FLUSH WITH LARGE VOLUME
OF WATER.REMOVE ANY SOURCE OF SPARK
S OF FLAME.PROVIDE ADEQUATE
EXHAUST.ABSORB MATERIAL

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EYE CONTACT.AVOID REPEATED OR
PROLONGED SKIN CONTACT.USE WITH ADEQUATE VENTILATION TO KEEP BELOW
TLV.KEEP CONTAINER CLOSED

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF CONTAINED IF NEEDED,ESPECIALLY IN CONFINED
AREAS
Ventilation:LOCAL - RECOMMENDED
Protective Gloves:RUB

BER
Eye Protection:FACE SHIELD/SAFETY GOGGLE
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:172F,78C
Vapor Pres:75
Vapor Density:3.0
Spec Gravity:0.902
Evaporation Rate & Reference:1.1 (N-BUTYL ACETATE =1)
Solubility in Water:MODERATE
Appearance and Odor:COLORLESS LIQUID WITH A SWEET ESTER ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXI
DIZERS

===== Disposal Considerations =====

Waste Disposal Methods:PLACE ABSORBED MATERIAL IN CONTAINERS SUITABLE
FOR SHIPPING TO DISPOSAL AREA

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.