

APCOX OIL CORP -- APCO 140 -- 8010-00-246-6112

=====
Product Identification
=====

Product ID:APCO 140

MSDS Date:01/01/1987

FSC:8010

NIIN:00-246-6112

MSDS Number: BDNHW

=== Responsible Party ===

Company Name:APCOX OIL CORP

Emergency Phone Num:405-236-5641

CAGE:KO826

=== Contractor Identification ===

Company Name:APCO OIL/OKLAHOMA CITY, OK 73101

CAGE:4A712

Company Name:APCOX OIL CORP

CAGE:KO826

==

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROCARBONS

Fraction by Wt: 100%.

ACGIH TLV:100 PPM, MFG

=====
Hazards Identification
=====

Effects of Overexposure:SLIGHT IRRIT TO MUCOUS MEMBRANES

=====
First Aid Measures
=====

First Aid:SKIN: WASH W/SOAP & WATER. INHAL: REMOVE PATIENT TO FRESH AIR. EYES: IMMEDIATELY FLUSH W/WATER FOR AT LEAST 15 MIN. INGEST: CALL MD IMMED. DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures
=====

Flash Point:141F TCC (60C)

Lower Limits:0.9

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM FOR CLASS III LIQUID FIRES

Fire Fighting Procedures:H*2O SPRAY INEFF, BUT MAY BE USED TO COOL CNTNRS

Unusual Fire/Explosion Hazard:IF H*2O USED FOR FIRE, FOG NOZ PREF. KEEP AWAY FROM HEAT & OPEN FLAME

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES

OF IGNITION. AVOID BREATHING VAPOR. VENTILATE AREA. REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions: DO NOT STORE ABOVE 120°F. STORE LG AMTS IN STRUCTURES MADE FOR NFPA CLASS III LIQUIDS.
Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID. DO NOT FLAME CUT, BRAZE OR WELD. DOT: COMBUSTIBLE LIQUID

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: VENTILATE TO KEEP AIR BELOW TLV
Ventilation: LOCAL, PREFERABLE. MECH, ACCEPTABLE
Protective Gloves: SOLVENT RESIST
Eye Protection: RECOMMENDED
Supplemental Safety and Health
MFG LISTS VAPOR PRESSURE AS 0.7 MMHG. MFG SUGGESTS TLV OF 100 PPM.

=====
Physical/Chemical Properties
=====

HCC: V4
Boiling Pt: B.P. Text: 361°F
Vapor Density: 5.2
Spec Gravity: 48.3
Evaporation Rate & Reference: 90.0 ETHER
Solubility in Water: NEGLIGIBLE
Appearance and Odor: CLEAR, WATER-WHITE. MILD NAPHTHA, NON-RESIDUAL
Percent Volatiles by Volume: 100.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid: YES
KEEP AWAY FROM STRONG OXIDIZERS SUCH AS PERMANGANATE
Stability Condition to Avoid: HEAT, OPEN FLAMES, IGNITION SOURCES

=====
Disposal Considerations
=====

Waste Disposal Methods: INCINERATION ACCORDING TO AIR POLLUTION REGULATIONS. DO NOT INCINERATE I

N CLOSED CONTANERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to thei
r
particular situation.