

DOW CORNING CORPORATION -- DOW CORNING S CATALYST -- 5970-00-251-8766

=====
Product Identification
=====

Product ID:DOW CORNING S CATALYST

MSDS Date:09/29/1988

FSC:5970

NIIN:00-251-8766

MSDS Number: BDNWR

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:3901 S. SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-

496-5900

Preparer's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:DIBUTYL TIN DILAURATE (AS TIN)

CAS:77-5

8-7
RTECS #:WH7000000
Fraction by Wt: 5.0%
OSHA PEL:S, 0.1 MG/M3
ACGIH TLV:S, 0.1 MG/M3; 8990

Ingred Name:CALCIUM CARBONATE
CAS:471-34-1
RTECS #:FF9335000
Fraction by Wt: 16.0%
OSHA PEL:10 MG/CUM,AS T DUST
ACGIH TLV:10 MG/CUM,AS T DUST

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND
RESPIRATORY
TRACT,REDNESS OR SWELLING OF EYES,SLIGHT BURNS OF SKIN.
CHRONIC:IRRITATION,DERMATITIS.
Explanation of Carcinogenicity:NO DATA PER MSDS
Effects of Overexposure:IRRITATES SKIN & EYES.
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:EYE AND SKIN:FLUSH WITH PLENTY OF WATER FOR ABOUT 15-20
MINUTES;SEEK MEDICAL HELP IF NEEDED. INHALATION:REMOVE TO FRESH
AIR. INGESTION:SEEK MEDICAL HELP IMMEDIATELY.

==
=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:>212F/100C
Extinguishing Media:WATER FOG,DRY CHEMICAL,FOAM.
Fire Fighting Procedures:SELF CONTAINED BREATHING APP./PROTECTIVE
CLOTHING.
Unusual Fire/Explosion Hazard:MAY RELEASE IRRITATING VAPORS DURING
COMBUSTION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT & CONTAIN
FOR DISPOSAL.

=====

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL & DRY PLACE.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED IF THERE IS AN ADEQUATE VENTILATION.

Ventilation:MECHANICAL(GENERAL) IS RECOMMENDED.

Protective Gloves:RUBBER/PLASTIC

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:APRON,EYE-WASH FACILITIES.

Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES;WASH
T

HOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

TLV:0.1MG/CUM BASED ON SN,THE TLV OF SN IS FOR SKIN.

==== Physical/Chemical Properties =====

HCC:N1

Vapor Pres: