

OCTAGON PROCESS INC. -- VV-C-846A TYPE I CUTTING FLUID -- 9150-00-252-6380

=====  
Product Identification  
=====

Product ID:VV-C-846A TYPE I CUTTING FLUID

MSDS Date:01/01/1987

FSC:9150

NIIN:00-252-6380

MSDS Number: BDNYB

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Emergency Phone Num:(201)945-9400

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:

596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM SULFONATE (AN IONIC PETROLEUM SULFONATE) MFR DID NOT GIVE %AGE.

Fraction by Wt: UNKN

ACGIH TLV:NOT SPECIFIED

Ingred Name:PETROLEUM OIL (ACGIH TLV FOR OIL MIST 5MG/CUM)THF MFR DID NOT GIVE PERCENTAGE.

Fraction by Wt: UNKN

ACGIH TLV:5MG/CUM

=====  
Hazards Identification  
=====

=====  
Effects of Overexposure:EYES:IRRIT;SKIN:IRRIT,POSSIBLE SKIN DISORDERS (DERMATITIS, FOLLICULITIS, OIL ACNE, SKIN CANCER)

=====  
First Aid Measures  
=====

=====  
First Aid:SKIN:REMOVE OIL BY WIPING TOROUGHLY WASH W/SOAP & WATER.  
EYES:WASH W/WATER, GET MEDICAL ATTN.

=====  
Fire Fighting Measures  
=====

=====  
Flash Point:380F (C.O.C.)

Extinguishing Media:ALCOHOL FOAM,CO\*2 DRY CHEMICAL,WATER

Fire Fighting Procedures:KEEP FIRE EX

POSED CONTAINERS COOL WITH WATER  
SPRAY

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID AND ABSORB ON SAND,EARTH  
ETC. DIKE SPILL AREA. KEEP OUT OF SEWERS,WATER COURSES

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN  
USE.DO NOT HANDLE,STORE NEAR SPARKS,OPEN FLAMES OR STRONG OXIDANTS.

Other Precaut

ions:WASH THOROUGHLY AFTER HANDLING.REMOVE CONTAMINATED  
CLOTHING AND LAUNDER BEFORE RE-USE.DISCARD OIL SOAKED SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MESA APPROVED SCBA IN CONFINED AREA.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN