

EUTECTIC CORP -- ALUTIN 51 FLUX -- 3439-00-255-4568

=====
Product Identification
=====

Product ID:ALUTIN 51 FLUX

MSDS Date:09/11/1989

FSC:3439

NIIN:00-255-4568

MSDS Number: BDPDF

=== Responsible Party ===

Company Name:EUTECTIC CORP

Address:40-40 172ND ST

City:FLUSHING

State:NY

ZIP:11358

Country:US

Info Phone Num:718-358-4000

Emergency Phone Num:718-358-4000

CAGE:72271

=== Contractor Identification

===

Company Name:EUTECTIC CORP

Address:9625-J SOUTHERN PINE BLVD

Box:City:CHARLOTTE

State:NC

ZIP:28273

Country:US

Phone:704-527-9800/ 800-221-1433

CAGE:72271

=====
Composition/Information on Ingredients
=====

Ingred Name:AMINOETHYLETHANOLAMINE

CAS:111-41-1

RTECS #:KJ6300000

Other REC Limits:NONE SPECIFIED

Ingred Name:AMMONIUM FLUOBORATE (SARA III)

CAS:13826-83-0

RTECS #:BQ6100000

Other REC Limits:NONE SPECIFIED

OSHA PEL:2.5 MG F/M3

ACGIH TLV:2.5 MG F/M3; 9192

EPA Rpt Qty:5

000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC OXIDE
CAS:1314-13-2
RTECS #:ZH4810000
Other REC Limits:NONE SPECIFIED
OSHA PEL:15MG/M3 TDUST/5 FUME
ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:CADMIUM FLUOROBORATE
CAS:14486-19-2
RTECS #:EV0525000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3/2 STEL
ACGIH TLV:1 MG/M3/2 STEL; 8990

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Effects of Overexposure:SKIN OR EYE CONTAC
T MAY CAUSE IRRITATION. FUMES
MAY CONTRIBUTE TO RESPIRATORY IRRITATION.

=====
===== First Aid Measures =====

First Aid:FLUSH AFFECTED AREA WITH WATER.REMOVE TO WELL VENTILATED
AREA. OBTAIN MEDICAL ASSISTANCE IF NECESSARY.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT WITH SKIN OR EYES. RINSE
THOROUGHLY WITH WATER IF CONTACT MADE.

=====
===== Handling and Storage =====

Handling and Sto

Precautions:REFER TO AWS PUBLICATION ANSI
Z49.1-198. KEEP FLUX SOLUTIONS IN TIGHTLY CLOSED GLASS OR PLASTIC
CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AIR-SUPPLIED TYPE IN CONFINED AREA.
Ventilation:LOCAL EXHAUST/MECHANICAL.
Protective Gloves:WELDER'S.
Eye Protection:PROTECTIVE SHIELD & LENS.
Supplemental Safety and Health
FORMULATION CHANGE FROM P/N IND A; ALUTIN 51-B SERIES IS NO LONGER
PRODUCED.

=====
==== Physical/Chemical Properties =====

HCC:B2
Solubility in Water:APPRECIABLE
Appearance and Odor:BROWN LIQUID AT ATMOSPHERIC CONDITION.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:COMPLEX,TOXIC FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:FLUSH THOROUGHLY WITH WATER. NORMAL INDUSTRIAL
WASTE PROCEDURE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.