View NSN Online: https://aerobasegroup.de/nsn/3439-00-255-4572

SUPERIOR FLUX AND MFG CO -- SUPERIOR NO.19; POWDER BRAZING FLUX -- 3439-00-255-4572

Product ID:SUPERIOR NO.19; POWDER BRAZING FLUX MSDS Date:02/21/1990 FSC:3439 NIIN:00-255-4572 MSDS Number: BDPDM === Responsible Party === Company Name: SUPERIOR FLUX AND MFG CO Address:95 ALPHA PARK City:CLEVELAND State:OH ZIP:44143-2201 Country:US Info Phone Num:216-461-3315 Emerge ncy Phone Num:216-461-3315 Preparer's Name: BRUCE B.HORVATH CAGE:87618 === Contractor Identification === Company Name: SUPERIOR FLUX AND MFG CO Address:6615 PARKLAND BLVD City:SOLON (FORMALLY CLEVELAND) State:OH ZIP:44139 Country:US Phone:440-349-3000 CAGE:87618 Ingred Name:LITHIUM CHLORIDE CAS:7447-41-8 RTECS #:0J5950000 Fraction by Wt: 10-15% Ingred Name: ZINC CHLORIDE (SARA III) CAS:7646-85-7 RTECS #: ZH1400000

Fraction by W

t: 3-8% OSHA PEL:1 MG/M3/2 STEL ACGIH TLV:1 MG/M3/2STEL FUME93 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:POTASSIUM CHLORIDE CAS:7447-40-7 RTECS #:TS8050000 Fraction by Wt: 30-70%

Ingred Name:SODIUM FLUORIDE (SARA III) CAS:7681-49-4 RTECS #:WB0350000 Fraction by Wt: 10-25% OSHA PEL:2.5 PPM F ACGIH TLV:2.5 MG F/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY OR G,I.TRACT OR NAUSEA,VOMITING AND LACK OF CO-ORDINATION.CHRONIC:INCREASED BONE DENSITY,HARDENING OF LIGAMENTS.

Explanation of Carcinogenicity:DATA PER MGF MSDS.

Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid:EYES AND SKIN:FLUSH WITH LARGE AMOUNT OF WATER FOR ABOUT 15-20 MINUTES;SEEK MEDICAL ATTENTION IMMEDIATELY.INHALATION:REMOVE TO FRESH AIR;CALL A PHYSICIAN.INGESTION:SEEK MEDICAL ATTENTION IMMEDIATELY.

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NONE

Extinguishing Media:NOT FLAMMMABLE ;USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG FOR SURROUNDING FIRE.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FUL

L PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:NONE EXPECTED

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; SWEEP UP OR VACUUM AND COLLECT FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENT ILATED

AREA.KEEP CONTAINER CLOSED WHEN NOT IN USE. Other Precautions:WASH THOROUGHLY AFTER EACH USE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR DUST/MIST IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA. Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV. Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES/GOGGLES Other Protective Equipment:PROTECTIVE CLOTHINGS.EYE-WASH FACILITIES,SAFETY SHOWER. Wo rk Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST/DUST.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health MSDS UNDATED

HCC:N1 Spec Gravity:2.34 Solubility in Water:COMPLETE Appearance and Odor:WHITE POWDER, MODERATELY HYDROSCOPIC

Stability Indicator/Materials to Avoid:YES ALKALINE MATERIALS, AMMONIA Stability

Condition to Avoid:HIGH TEMPERATURES Hazardous Decomposition Products:CHLORIDE, FLUORIDE, ZINC

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES;DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.