

NUODEX INC -- ANDEROL 401D SYNTHETIC INSTRUMENT OIL -- 9150-00-257-5449

=====  
Product Identification  
=====

Product ID:ANDEROL 401D SYNTHETIC INSTRUMENT OIL

MSDS Date:05/14/1986

FSC:9150

NIIN:00-257-5449

MSDS Number: BDPKM

=== Responsible Party ===

Company Name:NUODEX INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08854

Country:US

Info Phone Num:201-763-7173

Emergency Phone Num:201-

763-7173

CAGE:GO026

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

Company Name:NUODEX INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08854

Phone:(201) 763-7173

CAGE:GO026

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

=====  
Hazards Identification  
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:SEE SYMPTOMS OF OVEREXPOSURE  
Effects of Overexposure:LOW ORAL & DERMAL TOXICITY. MISTS OR FUMES FROM  
EXCESS HEATING MAY CAUSE IRRITATION,NAUSEA,VOMITING.  
Medical Cond Aggravated by Exposure:NONE GIVEN.

===== First Aid Measures =====

First Aid:SKIN-WASH W/SOAP & WATER. EYES-FLUSH W/WATER 15 MIN;CALL  
PHYSICIAN IF IRRIT DEVELOPS. INHAL-GET TO FRESH AIR,  
GIVE ARTIF  
RESPIR/OXYGEN IF REQD. INGEST-IF CONSCIOUS,INDUCE VOMITING,CALL  
PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:>450F  
Extinguishing Media:WATER SPRAY,DRY CHEM,FOAM,CARBON DIOXIDE  
Fire Fighting Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR  
SLF-CONTND BREATH APPARATUS & FULL TURN-OUT GEAR TO FIGHT FIRE.  
AVOID SPREADING LIQUID & FIRE BY WATER FLOODING.  
Unusual Fire/Explosion Hazard:EXPOS TO HEAT BUIL  
DS UP PRESSURE IN  
CLOSED CONTNRS. COOL W/WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:COVER W/AN INERT,ABSORBENT MATL & REMOVE TO  
DISPOSAL CONTNR. KEEP FM CONTAMINATING ANY LAKES,STREAMS,PONDS OR  
UNDERGROUND WATER SUPPLY.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE MAX RECOMMENDED  
OPERATING TEMP OF 450F/232C.MAY SOFTEN SOME PLASTIC & PAINT  
SURFACES.WIPE UP SPILL IMMED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED,USE APPROPRIATE NIOSH-APPROVED  
RESPIR PROTECT EQUIP.  
Ventilation:LOCAL EXHAUST & GEN MECH RECOMMENDED  
Protective Gloves:IMPERVIOUS  
Eye Protection:CHEM SPLASH GOGGLES OR FACE SHIELD  
Other Protective Equipment:EYE WASH FOUNTAIN;SAFETY SHOWER  
Work Hygienic Practices:WASH CONTAM CLOTH BEFORE REUSE.  
Supplemental Safety and Health

===== Physic

al/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>660F

Vapor Pres: