

GRAFO COLLOIDS CORPORATION -- MIL-L-3572A,LUBRICANT COLLOIDAL,GRADE
9150-00-261-7905

=====
Product Identification
=====

Product ID:MIL-L-3572A,LUBRICANT COLLOIDAL,GRADE

MSDS Date:01/01/1985

FSC:9150

NIIN:00-261-7905

MSDS Number: BDPPL

=== Responsible Party ===

Company Name:GRAFO COLLOIDS CORPORATION

Emergency Phone Num:(412)981-1773

CAGE:72872

=== Contractor Identification ===

Company Name:GRA

FO COLLOIDS CORP

Address:299 WILKS PLACE

Box:195

City:SHARON

State:PA

ZIP:16146

Country:US

CAGE:72872

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL

Fraction by Wt: 97.5%

RTECS #:VV7780000

Fraction by Wt: 2.0%

Ingred Name:DISPERSANT(DISPERSING AGENT);TLV UNSPECIFIED

Fraction by Wt: 0.5%

=====
Hazards Identification
=====

Effects of Overexposure:CONTRACT W/EYES MAY CAUSE IRRITATION AS WILL
REPEATED OR PROLONGED

GED SKIN CONTACT.

=====
===== First Aid Measures =====

First Aid:SEE A PHYSICIAN IF IRRITATION DEVELOPS IN EYES OR ON SKIN.

=====
===== Fire Fighting Measures =====

Flash Point:315F-(C.O.C)

Lower Limits:UNK

Upper Limits:UNK

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER SPRAY OR FOG.

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIP.COOL HEAT-EXPOSED
CONTNR W/H*20

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG
OXIDANTS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:KEEP OUT OF WATERWAYS & STREAMS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT & OPEN
FLAMES.KEEP COVERED WHEN NOT IN USE.

Other Precautions:MAY CAUSE BLACK STAINS ON FABRICS WHICH ARE DIFFICULT
TO REMOVE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR-SUPPLIED EQUIPMENT IF EXPOSED TO HOT FUMES.

Ventilation:LOCAL EXHAUST IF NEEDED TO REMOVE HOT FUMES.

Protective Gloves:OIL-RESISTANT

Eye Protection:GOGGLES

Other Protective Equipment:OIL-RESISTANT APRON/COAT FOR PROTECTION OF
PERSONAL CLOTHING

Supplemental Safety and Health

MSDS NOT DATED; SPEC REFERENCE: MIL-L-3572A, GRADE A; COMPONENTS &
THEIR % WT PER MFR LETTER DATE SEPTEMBER 19,84.

=====
===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:UNK

Vapor Density

:UNK
Spec Gravity:0.91
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK LIQUID WITH PETROLEUM OIL ODOR.
Percent Volatiles by Volume:UNK

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS (OXYGEN,CHLORINE)
Hazardous Decomposition Products:INCOMPLETELY BURNED CARBON PRODUCTS,
CO*2, CO.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERAT
OR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice
to verify and
assume responsibility for the suitability of this information to their
particular situation.