

GRAFO COLLOIDS CORPORATION -- MIL-L-3572A,LUBRICANT COLLOIDAL,GRADE B --
9150-00-261-7906

=====
Product Identification
=====

Product ID:MIL-L-3572A,LUBRICANT COLLOIDAL,GRADE B

MSDS Date:01/01/1987

FSC:9150

NIIN:00-261-7906

MSDS Number: BDPPM

=== Responsible Party ===

Company Name:GRAFO COLLOIDS CORPORATION

Emergency Phone Num:(412)/981-1773

CAGE:72872

=== Contractor Identification ===

Company Name

e:GRAFO COLLOIDS CORP

Address:299 WILKS PLACE

Box:195

City:SHARON

State:PA

ZIP:16146

Country:US

CAGE:72872

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM OIL

Fraction by Wt: 87.5%

RTECS #:VV7780000

Fraction by Wt: 10.0%

Ingred Name:DISPERSANT(DISPERSING AGENT);TYPE UNSPECIFIED

Fraction by Wt: 2.5%

ACGIH TLV:UNKNONW

=====
Hazards Identification
=====

Effects of Overexposure:CONTACT W/EYES MAY CAUSE IRRITATION AS WI

LL

REPEATED OR PROLONGED SKIN CONTACT.

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET;SEE A PHYSICIAN IF IRRITATION DEVELOPS IN EYES OR ON SKIN.

===== Fire Fighting Measures =====

Flash Point:340F/171C (C.O.C

Lower Limits:UNK

Upper Limits:UNK

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER S
PRAY OR FOG.

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIP.COOL HEAT-EXPOS
CONTNR W/H*2O

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.
EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT
ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG
SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITI
ES.KEEP OUT
OF WATERWAYS & STREAM

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT & OPEN
FLAMES.KEEP COVERED WHEN NOT IN USE.

Other Precautions:MAY CAUSE BLACK STAINS ON FABRICS WHICH ARE DIFFICULT
TO REMOVE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR-SUPPLIED EQUIPMENT IF EXPOSED TO HOT FUMES

Ventilation:LOCAL EXHAUST IF NEEDED TO REMOVE HOT FUMES

Protect

ive Gloves:OIL-RESISTANT

Eye Protection:GOGGLES

Other Protective Equipment:OIL-RESISTANT APRON/COAT FOR PROTECTION OF PERSONAL CLOTHING

Supplemental Safety and Health

MSDS NOT DATED;SPEC REFERENCE: MIL-L-3572A, GRADE B,COMPONENTS & THEIR % WT PER MFR LETTER DATE SEPTEMBER 19,84

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:UNK

Vapor Density:UNK

Spec Gravity:0.95

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK LIQUID WITH PETROLEUM OIL ODOR.

Percent Volatiles by Volume:UNK

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS (OXYGEN,CHLORINE)

Hazardous Decomposition Products:INCOMPLETELY BURNED CARBON PRODUCTS, CO*2, CO.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation

n.