

GEARHART INDUSTRIES INC -- 10-352 RUBBER TO METAL CEMENT -- 8040-00-261-8450

=====
Product Identification
=====

Product ID:10-352 RUBBER TO METAL CEMENT

MSDS Date:01/01/1987

FSC:8040

NIIN:00-261-8450

MSDS Number: BDPRN

=== Responsible Party ===

Company Name:GEARHART INDUSTRIES INC

Address:1100 EVERMAN RD

Box:1936

City:FORT WORTH

State:TX

ZIP:76101

Country:US

Info Phone Num:815-968-9661

Emergency

Phone Num:815-968-9661

CAGE:26999

=== Contractor Identification ===

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

Company Name:GEARHART INDUSTRIES INC

Address:1100 EVERMAN RD

Box:1936

City:FORT WORTH

State:TX

ZIP:76101

Country:US

CAGE:26999

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 74%

ACGIH TLV:500PPM

=====
Hazards Identification

=====
Effects of Overexposure:EYE & SKIN IRRIT,INHL.RESULTS IN LOSS OF
COORDINATION,DROWSINESS,HDACH,DIZZINESS,NAUSEA,VOMITING

=====
First Aid Measures

First Aid:EYES-FLUSH W/WATER,CALL PHYSICIAN. SKIN-FLUSH W/SOAP & WATER.
INHALATION, REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, GIVE
ARTIFICIAL RESPIRATION. IF SWALLOWED, INDUCE VOMITING. CALL DR.

=====
Fire Fighting Measures

F
Flash Point:14F TCC -10C
Extinguishing Media:DRY CHEM, CARBON DIOXIDE, ALCOHOL FOAM.
Fire Fighting Procedures:SELF-CONTND BREATHNG APPARAT W/A FULL PIECE
OPERAT IN (SUPP)
Unusual Fire/Explosion Hazard:MATR IS HIGHLY VOLATILE & READILY GIVES
OFF VAPS WHICH MAY TRAVL & CAUS FLASH FIRES OR BE IGNIT(SUP)

=====
Accidental Release Measures

Spill Release Procedures:ELIMINATE IGNITION SOURCE, STOP SPILL AT
SOURCE, CONTAIN SPILL BY DIKE, ABSORB WITH PAPER, V
ERMICULITE,
FLOOR ABSORBENT & TRANSFER TO HOOD.

=====
Handling and Storage

Handling and Storage Precautions:KEEP CONTAINER CLOSED.USE ONLY
W/ADEQUATE VENTILATION.KEEP AWAY FROM HEAT, SPARK & OPEN FLAMES.
Other Precautions:EMPTY CONTAINERS CAN BE HAZARDOUS SINCE RESIDUE IS
RETAINED. DISPOSE OF PROPERLY.

=====
Exposure Controls/Personal Protection

Respiratory Protection:YES-TLV LEVELS ARE EXCEEDED (NIOSH/MESA APPRVD)
Ventilation:PROVID SUFFICIENT MECH (GEN) AND/OR LOC EXHAUST VENTIL TO
KP
Protective Gloves:IMPERVIOUS
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:IMPERVIOUS CLOTHING & FACE SHIELD
Supplemental Safety and Health
SPEC. FIRE FIGHT PROCED: PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE
MODE

=====
Physical/Chemical Properties

HCC:F2
Boiling Pt:B.P. Text:760MM-163F
Vapor Pres:119
Vapor Density:2.4
Spec Gravity:.90
Evaporation Rate & Referen

ce:ETHYL ETHER 2.80
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER LIQUID
Percent Volatiles by Volume:96%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT W/STRONG OXIDIZING AGENTS,STRONG ALKALIES.
Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS,CO,CARBON
DIOXIDE,ETC.

===== Disposal Considerations =====

Waste Disposal Methods:LIQUID INCINERATION.

Disclaimer (p
rovided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.