

HOBART BROTHERS COMPANY -- HOBART 335A -- 3439-00-262-2652

===== Product Identification =====

Product ID:HOBART 335A

MSDS Date:01/01/1987

FSC:3439

NIIN:00-262-2652

MSDS Number: BDPWR

=== Responsible Party ===

Company Name:HOBART BROTHERS COMPANY

Address:600 W. MAIN STREET

City:TROY

State:OH

ZIP:45373

Info Phone Num:513-339-6000

Emergency Phone Num:513-339-6000

CAGE:28835

=== Contractor Identificat

ion ===

Company Name:HOBART BROTHERS CO

Address:600 W MAIN ST HOBART SQUARE

Box:City:TROY

State:OH

ZIP:45373

Country:US

Phone:513-339-6000

CAGE:28835

===== Composition/Information on Ingredients =====

Ingred Name:MAGNESIUM SILICATE;WT% RANGE 0-5%;ALL TLV DATA SUPPLIED BY
MFG;DATA FOR FLUX COMPONENTS.

Fraction by Wt: 5%

Other REC Limits:NONE

OSHA PEL:10MG/M*3/MG-TOT DUST

ACGIH TLV:10MG/M*3/MG-TOT DUST

Ingred Name:CELLULOSE (PAPER FIBER)

CAS:9004-34-6

RTECS #:FJ5691460

Fra

ction by Wt: 30%
Other REC Limits:NONE
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 30%
Other REC Limits:NONE
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:FERRO MANGANESE;WT % RANGE 2-6%
CAS:12604-53-4
RTECS #:OO9286520
Fraction by Wt: 5%
Other REC Limits:NONE
OSHA PEL:1MG/M*3(MN FUMES)
ACGIH TLV:1MG/M*3(MN FUMES)

Ingred Name:SODIUM-POTASSIUM SILICATE;WT % RANGE 15-30%;NOTE:IRON CORE
WE
LDING ROD;DATA IS FOR FLUX
Fraction by Wt: 30%
Other REC Limits:NONE
OSHA PEL:80MG/M*3(AMORPHOUS)
ACGIH TLV:10MG/M*3(AMORPHOUS)

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:NONE NOTED BY MANUFACTURER:LOW TOXICITY AND LOW
HAZARD TO HEALTH;WELDING FUMES MAY CAUSE FAINTNESS.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/0*
2 IF NEED.CALL
PHYSICIAN (USE STANDARD LOW TOXICITY CHEMICAL FIRST AID)

===== Fire Fighting Measures =====

Extinguishing Media:NON FLAMMABLE:USE MEDIA SUITABLE FOR SURROUNDING
FIRE.
Fire Fighting Procedures:NONE NOTED
Unusual Fire/Explosion Hazard:NONE NOTED

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE VENTILATION, ELIMINATE DUST.
SWEEP/SHOVEL MATERIAL INTO APPR CONTAINERS.

=====

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED. PROTECT FROM PHYSICAL DAMAGE.
Other Precautions:MAINTAIN STANDARD HYGIENE FOR CHEMICAL HANDLING. WELDING SPARKS MAY IGNITE COMBUSTIBLE PRODUCTS.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:WELD FUME RESPIRATOR/AIR LINE RESPIRATOR IF EXCEED TLV, 5 PPM (FUMES
Ventilation:IF IN CONFINED SPACE, LOCAL VENTILATION.
Protective Gloves:LEATHER
Eye Protection:ABSORPTIVE
Other Protective Equipment:LEATHER APRON
Supplemental Safety and Health
TYPE 6011 CLASS I, WELDING ELECTRODES. THE CORE WIRE IS IRON, WHICH IS 80% OF THE TOTAL ROD WEIGHT; INGREDIENTS DATA IS FOR FLUX COVERING IN THE ROD, CLASS E6011. WELDING FUME TLV: 5MG/CUM.

==== Physical/Chemical Properties =====

HCC:N1
Appearance and Odor:WELDING ROD, ODORLESS

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

==== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL. HANDLE AND DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The Unit

ed States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.