

HENRY W W CO -- 232 ASPHALT CUTBACK ADHESIVE SR,MMM-A-110B -- 8040-00-262-9009  
===== Product Identification =====

Product ID:232 ASPHALT CUTBACK ADHESIVE SR,MMM-A-110B

MSDS Date:02/01/1988

FSC:8040

NIIN:00-262-9009

MSDS Number: BDQDN

=== Responsible Party ===

Company Name:HENRY W W CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-2629

Country:US

Info Phone Num:213-583-4961 / FAX 21

3-582-8451

Emergency Phone Num:213-583-4961

CAGE:11761

=== Contractor Identification ===

Company Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 28.0%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 8990

Ingred Name:ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OS

HA PEL, SEE  
29CFR 1910.1101)

CAS:1332-21-4

RTECS #:CI6475000

Fraction by Wt: 7.0%

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:0.5 FIBERS/CC; A1;89

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====  
Hazards Identification =====

Effects of Overexposure:INHALATION:POSSIBLE ASPHYXIATION.EYE IRRITANT

=====  
First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF NORMAL RESPIRATION HAS STOPPED, APPLY ARTIFICIAL RESP. IF IRRITATION PERSISTS GET MEDICAL ATTN.

=====  
Fire Fighting Measures =====

Flash Point:56.0F,13.3C

Lower Limits:1%

Extinguishing Media:FOAM, CO\*2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:NONE KNOWN. USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:VAPORS ARE FLAMMABLE IF ALLOWED TO COLLECT & CONCENTRATE. ADHESIVE WILL FLOAT TO SURF OF WATER & MAINTAIN FLAME. WATER CAN SPREAD FLAME. CLOSED CONTAINERS MAY (SUPDAT)

=====  
Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF COMBUSTION IN THE AREA. CLEAN UP SPILL AS SOON AS POSSIBLE.

=====  
Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME.

Other Precautions:DOT:FLAMMABLE

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:MFG STATES PROPER VENTILATION IF SUFFICIENT

CIENT

Ventilation:TO KEEP VAPOR CONCENTRATION BELOW MFG REC TLV OF 350 PPM

Supplemental Safety and Health

THE BOILING PT & VAPOR PRESSURE ARE FOR THE SOLVENT PORTION ONLY. THIS PRODUCT CONTAINS ASBESTOS,DETERMINED TO BE A HUMAN CARCINOGEN.PROD MEETS MMM-A-110B TY II.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:>257F,>125C

Vapor Pres:SEE ING

Vapor Density:HVR/AIR

Spec Gravity:0.946

Evaporation Rate & Reference:SLOWER THAN ETHER

S

solubility in Water:NOT KNOWN

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:40

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN.

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME AND ALL OTHER IGNITION SOURCES.

Hazardous Decomposition Products:INCOMPLT COMBSTN:CO;NORM COMBSTN:BLK SMOKE, CO\*2 & WATER

===== Disposal Considerations =====

Waste Dis

posal Methods:SCOOP ALL MATERIAL INTO METAL CONTAINERS & REMOVE TO SAFE PLACE. MFG REC ALLOWNG TO DRY BY EVAPORATION OR DISPOSAL BY BURNING, IF PERMITTED. FOLLOW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability

for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.