

UNIROYAL, INC., ADHESIVES & COATINGS DEPARTMENT -- ROYAL M6314; RUBBER BASE ADHESIVE; TYPE I -- 8040-00-262-9028

=====
Product Identification
=====

Product ID:ROYAL M6314; RUBBER BASE ADHESIVE; TYPE I

MSDS Date:01/01/1985

FSC:8040

NIIN:00-262-9028

MSDS Number: BDQFD

=== Responsible Party ===

Company Name:UNIROYAL, INC., ADHESIVES & COATINGS DEPARTMENT

Address:312 N HILL ST

Box:2000

City:MISHAWAKA

State:IN

ZIP:46544-1399

Country:US

CAGE:KO958

=== Contractor Identification ===

Company Name:UNIROYAL PLASTICS CO INC ENGINEERED SYSTEMS UNIT

Address:312 N HILL ST

Box:2000

City:MISHAWAKA

State:IN

ZIP:46544-1399

Country:US

Phone:219-256-8376

CAGE:00333

Company Name:UNIROYAL, INC., ADHESIVES & COATINGS DEPARTMENT

Address:312 N HILL ST

Box:2000

City:MISHAWAKA

State:IN

ZIP:46544-1399

Country:US

CAGE:KO958

=====
Composition/Information on Ingredients
=====

Ingred Name:TEXTILE SP

IRITS

Fraction by Wt: 60%.

ACGIH TLV:500 PPM (MFR)

===== Hazards Identification =====

Effects of Overexposure:EYE & THROAT IRRIT, HEADACHE & NAUSEA AT 2-3
TIMES THE TLV, NARCOSIS AT HIGH EXPOS

===== First Aid Measures =====

First Aid:FOR OVER EXPOSURE TO VAPORS, REMOVE TO FRESH AIR. NO SYSTEMIC
POISONING TO BE EXPECTED. IF SPLASHED IN EYES OR INGESTED, CALL MD
IMMED.

===== Fire Fighting Measures =====

Flash Point:-45F

Lower Limits:1.4

Upper Limits:7.6

Extinguishing Media:CO*2 OR OTHER MEDIA SUITABLE FOR SOLVENT FIRES

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. KEEP AWAY FROM FIRE,
SPARKS, OR SOURCES OF HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP SPILLAGE W/WASTE. TRANSFER MATERIAL
FROM LEAKING CONTAINERS TO AIR TIGHT METAL CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:EXTREMELY FLAMMABLE. KEEP AWAY FROM
FIRE, SPARKS OR SOURCES OF HEAT.

Other Precautions:RED LABEL REQUIRED WHEN SHIPPING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQ'D IF VAPORS KEPT BELOW TLV. NIOSH/MSHA
APPRVD RESP IF NEC.

Ventilation:MFR RECM MECH, SUFFICIENT TO KEEP BELOW TLV.

Protective Gloves:POLYETHYLENE

Eye Protection:GLASSES OR GOGGLES

Other Protective Equipment:HAND CREAM

S OR EMOLLIENTS USEFUL
Supplemental Safety and Health
VAPOR DENSITY: 3.0-4.0. MFR SUGGESTS TLV OF 500 PPM.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:100-399F
Spec Gravity:0.96
Evaporation Rate & Reference:2.5 (ETHER)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:RED LIQUID W/ALIPHATIC HYDROCARBON ODOR
Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM BURNING OR BURIAL. DISPOSE IAW FED., STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.