

CSD INC. -- CALIBRATING FLUID -- 6850-00-264-5771

===== Product Identification =====

Product ID:CALIBRATING FLUID

MSDS Date:09/26/1986

FSC:6850

NIIN:00-264-5771

MSDS Number: BDQKG

=== Responsible Party ===

Company Name:CSD INC.

Address:420 SEABOARD DRIVE

Box:687

City:METTHEWS

State:NC

ZIP:28105

Country:US

Info Phone Num:704-821-9822

Emergency Phone Num:704-821-9822

CAGE:JO933

=== Contractor Identification ===

Company Name:CSD INC.

Address:5 HACKBERRY LANE

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:JO933

Company Name:CSD INC. (PRE 1985 NAME: MATHEWS, INC)

Address:420 SEABOARD DRIVE

Box:City:MATTHEWS

State:NC

ZIP:28105-5073

Country:US

Phone:704-821-9822

CAGE:5W216

===== Composition/Information on Ingredients =====

Ingred Name:C9-C11 PARAFFINS, CYCLOPARAFFINS & AROMATICS

Fraction by Wt: 100%

ACGIH TLV:5 MG/CUM (MIST)

=====

Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT. MOST
HAZARDOUS EXPOSURE;EXPOSURE IS TO AIRBORN MIST OR OTHER ASPIRATION
OF LIQUID INTO LUNGS. PROLONGED/REPEATED OVEREXPOSURE MAY CAUSE
LIVER OR KIDNEY DAMAGE.
Effects of Overexposure:EYE:MILD IRRITATION. SKIN:DRYING,DEFATTING WITH
PROLONGED/REPEATED CONTACT.
IN
HALED:HEADACHE,NAUSEA,CONFUSION,DROWINESS. ASPIRATION OF LIQUID
MAY CAUSE CHEMICAL PNOUMONITIS. INGESTED:G/I IRRITATION,NA
USEA,POSSIBLE VOMITING.
Medical Cond Aggravated by Exposure:NONE EXPECTED

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:REMOVE CONTAMINATED
CLOTHING (LAUNDER BEFORE REUSE) AND THOROUGHLY AREA OF CONTACT WITH
SOAP AND WATER. INHALED:REMOVE FROM EXPOSURE.RESUSCITATE OR GIVE
OXYGEN IF NEE D
EE THEN GET MEDICAL ATTENTION. INGESTED:DO NOT
INDUCE VOMITING. GET MEDICAL ATTENTION. IF ANY IRRITATION PERSISTS
OR IS SEVERE,GET MEDICAL CARE.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105F
Lower Limits:0.9
Upper Limits:6.0
Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL,WATER FOG. WATER
MAY BE INEFFECTIVE AND MAY SPREAD FIRE IF IMPROPERLY USED.
Fire Fighting Procedures:USE SELF CONTAINED BREATHING
APPARATUS,E
SPECIALLY IN ENCLOSED AREAS. WATER SPRAY MAY BE USED TO
COOL FIRE EXPOSED CONTAONERS AND EQUIPMENT.
Unusual Fire/Explosion Hazard:WHEN HEATED SUFFICIENTLY,VAPORS MAY FORM
EXPLOSIVE MIXTURES WITH AIR. SATURATED NEWSPAPERS,RAGS,ETC. MAY
UNDERGO SPONTANOUS COMBUSTION.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. USE APPROPRIATE
PROTECTIVE EQUIPMENT. CONTAIN LEAK. PREVENT LEAK FROM ENTERING
SEWER, WATER

WAY,ETC. RECOVER AS LIQUID. REPORT SPILL IF
APPROPRIATE.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL AREA AWAY FROM OXIDIZERS
AND IGNITION SOURCES. DETACHED STORAGE PREFERRED. GROUND CONTAINERS
DURING TRANSFER.

Other Precautions:"EMPTY" CONTAINERS MAY CONTAIN RESIDUE AND/OR FUMES
WHICH ARE EXPLOSIVE.DO NOT CUT,WELD,ETC.

===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:NOT EXPECTED TO BE NECESSARY. USE NIOSH/MSHA
RESPIRATOR IF PRODUCT IS MISTED OR IF TLV/PEL IS EXCEEDED.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV/PEL IF
NORMAL ROOM VENTILATION IS IN SUFFICIENT.

Protective Gloves:RUBBER,PLASTIC,OR OTHER IMPERVIOUS

Eye Protection:SAFETY GLASSES OR SPLASH GOGGLES.

Other Protective Equipment:SAFETY SHOWER, EYE WASH, APRON.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID
UNNECESSARY CONT

ACT.

Supplemental Safety and Health

MSDS EFFECTIVE:9/26/86; SPEC REFERENCE: MIL-C-7024, TYPE II

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:316F/158C

Vapor Pres: