

ALLIED-SIGNAL INC, ENGINEERED MATERIALS SECTOR -- GENETRON 12 -- 6830-00-264-5913
===== Product Identification =====

Product ID:GENETRON 12

MSDS Date:08/01/1995

FSC:6830

NIIN:00-264-5913

MSDS Number: BDQLH

=== Responsible Party ===

Company Name:ALLIED-SIGNAL INC, ENGINEERED MATERIALS SECTOR

Address:COLUMBIA RD AND PARK AVE

Box:1087R

City:MORRISTOWN

State:NJ

ZIP:07960

Country:US

Info Phone Num:800-

522-8001

Emergency Phone Num:800-522-8001

CAGE:1L164

=== Contractor Identification ===

Company Name:ALLIED-SIGNAL INC

Box:2332R

City:MORRISTOWN

State:NJ

ZIP:07962-2332

Country:US

Phone:201-455-4414

CAGE:1L164

Company Name:CFC RECOVERY SYSTEMS INC (770-984-2292)

Box:UNKNOW

CAGE:0UJL7

===== Composition/Information on Ingredients =====

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 100%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA

Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

===== Hazards Identification =====

Effects of Overexposure:DEPRESSES CNS,IRRITATS RESPIR TRACT;HIGH CONCS
CAUSE CARDIAC ARRYTHMIA,ASPHYXIATION AND DEATH.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:PRESENC IN FIRE DOES NOT HINDER USE OF ANY STANDARD
MEDIUM.
Fire Fighting Procedures:SELF-CNTND BRTHG APP.H*2O TO DISPERSE
V
APORS/COOL EXPOS CONT
Unusual Fire/Explosion Hazard:CONTACT W.REACTV METALS(MOLTEN AL,BA/LI
FINES)WILL PRODUCE RAPID EXOTHERMIC REACTIONS.

===== Accidental Release Measures =====

Spill Release Procedures:IF LARGE QUANTITY IS RELEASED,VACATE PREMISES
AND ALLOW TO DISSIPATE.NOTE TLV

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT.OUTDOOR STORAGE
PERMITTED.PROTECT CYLINDERS & TUBING
FROM PHYSICAL DAMAGE;DO NOT
PUNCTURE.USE AUTHORIZED CYLINDERS ONLY.
Other Precautions:HALOCARBONS IN CONFINED/ENCLOSED SPACES REQUIRE
WELL-VENTILATED DRAFT AS THE GAS DEPLETES OXYGEN WHICH IS NECESSARY
FOR BREATHING.CONTAC IN EYES/ON SKIN CAN CAUSE FROSTBITE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS IF NOT IN
WELL VENTILATED AREAS.
Ventilation:LOCAL EXHAUST AT FILLING ZONES.MECHANICAL AT STORA

GE AREAS.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

ITEM MEETS REQUIREMENTS FOR TYPE 12 UNDER FED SPEC BB-F-1421.

===== Physical/Chemical Properties =====

HCC:G3

Boiling Pt:B.P. Text:-22F,-30C

Melt/Freeze Pt:M.P/F.P Text:-252F,-158C

Vapor Pres:35 PSI

Vapor Density:4.26

Spec Gravity:1.325

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS LIQUEFIED GAS WITH FAINT ETHEREAL ODOR

Percent Volatiles by Volume:100

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

POWDERED AL,MG. ATTACKS MG AND ITS ALLOYS.

Stability Condition to Avoid:DECOMPOSES AT GAS FLAME TEMPERATURE GIVE
HALOGENS,HALO-ACIDS

Hazardous Decomposition Products:TOXIC SUBSTANCES BY HIGH
HEAT,E.G.FLUORIDES,CARBONYL HALIDES

===== Disposal Considerations =====

Waste Disposal Methods:FOR MODERATE QUANTITIES PERMIT TO EVAPORATE IN
AIR AT SLOW RATE,
SO AS NOT TO EXCEED TLV.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to

their
particular situation.