View NSN Online: https://aerobasegroup.de/nsn/6810-00-264-6717 OCTAGON PROCESS INC -- O-P-559 -- 6810-00-264-6717 ============ Product Identification ========================= Product ID:O-P-559 MSDS Date:01/01/1985 FSC:6810 NIIN:00-264-6717 MSDS Number: BDQVZ === Responsible Party === Company Name: OCTAGON PROCESS INC Address:596 RIVER ROAD City:EDGEWATER State:NJ ZIP:07020-1105 Country:US Info Phone Num:201-945-9400 Emergency Phone Num:201-945-9400 CAGE:82925 === Contractor Identifica tion === Company Name: OCTAGON PROCESS INC. Address:596 RIVER ROAD Box:City:EDGEWATER State:NJ ZIP:07020 Country:US Phone:201-945-9400 CAGE:82925 ======= Composition/Information on Ingredients ======== Ingred Name:POTASSIUM BICHROMATE (SARA III) CAS:7778-50-9 RTECS #:HX7680000 Fraction by Wt: 100% OSHA PEL:C,0.1 MG/M3 CRO3 ACGIH TLV:0.5 MG CR/M3; 9293 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS ============= Hazards Identification ========================

Effects of Overexposur

e:MAY CAUSE IRRIT OF MUCOUS MEM OR SKIN. INGEST: LG QTY MAY BE FATAL
======================================
First Aid:SKIN: FLUSH AREA W/WATER. REMOVE CONTAMINATED CLOTH. EYE: IRRIGATE EYES FOR 15 MIN. INGEST: GIVE MAGNESIA, CHALK OR WHITING SUSPEND IN WATER. FOLLOW W/EMETIC. GIVE OLIVE OIL OR MUCILAGINOUS DRINK. INH AL: IRRIGATE NASAL PASSAGE & MOUTH W/SALT-WATER.
======================================
Flash Point:N ONE
Extinguishing Media:WATER Fire Fighting Procedures:FLUSH W/WATER Unusual Fire/Explosion Hazard:WILL NOT BURN OR SUPPORT COMBUSTION
======== Accidental Release Measures ==========
Spill Release Procedures:SOLID, SCOOP UP. FLUSH AREA W/WATER.
======================================
Handling and Storage Precautions:STORE IN DRY AREA WHERE FLOOR CAN BE FLUSHED W/WATER IN EVENT OF SPILL. PERSONAL HYGIENE IMPORTANT. Other Precautions:AVOID CO NTACT W/SKIN OR EYES. AVOID BREATHING VAPORS OR MISTS. DO NOT TAKE INTERNALLY. SEE MCA SAFETY SHEET SD-46 ON CHROMATES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:US BUR MINES 2175 MODEL 7100 DUST RESP Ventilation:LOCAL OR MECHANICAL AS NEEDED TO MEET TLV Protective Gloves:RUBBER Eye Protection:CHEM SAFETY GOGGLES Other Protective Equipment:RUBBER APRON SLEEVES & RUBBER SAFETY SHOES. SAFETY SHOWER. Supplemental Safety and Health

====

======= Physical/Chemical Properties =========
HCC:D1 Spec Gravity:2.7 Appearance and Odor:CRYSTALLINE FREE FLOWING, ORANGE-RED, NO ODOR
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR OXIDIZABLE MATERIALS Hazardous Decomposition Products:NONE
======= Disposal Considerations ==========

Waste Disposal Methods:HEXAVALENT: REDUCE TO TRIVALENT-PRECIPITATE AS HYDROUS CHRO

MIC OXIDE. CAN USE REDUCING AGENTS SUCH AS; SODIUM SULFITE OR BISULFITE, SO\*2, FESO\*4. NEUTRALIZE TO PH OF 7 W/SODA ASH OR CAUSTIC SODA. OBSE RVE LOCAL, STATE, FED REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use

. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.