

SHERWIN-WILLIAMS CO -- V93 V P1 EPOXY PRIMER-PART B -- 8010-00-264-8866

=====
Product Identification
=====

Product ID:V93 V P1 EPOXY PRIMER-PART B

MSDS Date:01/01/1985

FSC:8010

NIIN:00-264-8866

MSDS Number: BDQWZ

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO

Address:101 PROSPECT AVE N W

City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Info Phone Num:216-566-2902

Emergency Phone Num:

216-566-2917

CAGE:54636

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

=====
Composition/Information on Ingredients
=====

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000

Fraction by Wt: 50%

OSHA PEL:S,200 PPM

ACGIH TLV:S, 5 PPM; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBU

TYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 10%

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:VAP:H1 CONC ANESTH; SKIN & RESP

IRRIT; MAY

CAUSE LIGHTHEADEDNESS & STAGGERING

===== First Aid Measures =====

First Aid:REMOVE FR EXPOS; RESTORE BREATH; KEEP QUIET & WARM; EYES:

FLUSH W/H*2O 15 MIN. WASH AFFCTD AREA W/H*2O REMOVE CONTAMTD CLOTH
& WASH BEFORE REUSE.

===== Fire Fighting Measures =====

Flash Point:81 F (PMCC)

Lower Limits:1.0

Extinguishing Media:CO*2,DRY CHEMICAL, FOAM

Fire Fighting Procedures:SELF-CNTND BREATH APPARAT; H*2O M

AYBE

INEFFECT;USE FOG NOZZ

Unusual Fire/Explosion Hazard:ISOLATE FR IGNIT SOURCES; CONTNRS MAY

EXPLODE; SPEC PRECAUTNS-HOT SURFACE APPLICA; H*2O COOL CONTNRS

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. VENTILATE & REMOVE

W/INERT ABSORBENT

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE LABEL, KEEP FROM ALL

IGNITION SOURCES. DO NOT TRANSFR

TO OTHER CONTAINERS FOR STORAGE.

SYMPT FROM OVEREXPOS TO DECOMP PROD NOT IMMED APPARNT

Other Precautions:USE ADE VENTIL+AVOID SKIN CNTCT/WASH AFT USE; CLOSE WHEN NOT USE; RESP PRTCT WHEN ABRADNG,WEKDNG; DONT APPLY TO CHILDS ARTCLS OR SURF TO WHCH CHILD EXPOSD. USE APPRVD BONDNG & GROUND PROCEDR

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD DEVICE FOR MIST & VAPORS IF NECESSARY

Ventilation:LOCAL PREFERABLE. GENERAL ACCEPTABLE. SPECIAL REQD

Protective Gloves:PRLNGD/RPTD EXP

Eye Protection:SAF/GOGGS W/UNPERFD SDSHL

Supplemental Safety and Health

PART B OF A 2-PART PRODUCT; PART A IS E90 R P3. VAPOR PRESSURE GIVEN IS FOR METHYL ISOBUTYL KETONE.KEY1:J1.

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:237-289 F

Vapor Pres:16.

Vapor Density:>1.0

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:76.0

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:FIRE:CO*2, CO, OXIDES OF NITROGEN

=====
===== Disposal Considerations =====

Waste Disposal Methods:INCIN IN APPVD FACILITY. DO NOT INCIN CLOSD CONTAINER. DISPOSE IN ACCORD W/FED, STATE & LOCAL REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.