View NSN Online: https://aerobasegroup.de/nsn/6810-00-264-9020

VIRGINIA CHEMICALS INC. -- SODIUM SULFITE, ANHYDROUS -- 6810-00-264-9020

Product ID:SODIUM SULFITE, ANHYDROUS MSDS Date:03/01/1987 FSC:6810 NIIN:00-264-9020 **MSDS Number: BDQZZ** === Responsible Party === Company Name: VIRGINIA CHEMICALS INC. Address:801 WATERSTREET City:PORTSMOUTH State:VA ZIP:23704 Country:US Info Phone Num:804-484-5000 Emergency Phone Num:804-484-5000 CAGE:87698 === Contractor Identification === Company Name: VIRGINIA CHEMICALS INC Address:801 WATER ST Box:City:PORTSMOUTH State:VA ZIP:23704 Country:US Phone:804-893-3247 CAGE:87698

Ingred Name:SODIUM SULFITE,ANHYDROUS CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: 97.5% OSHA PEL:5MG/CUM (DUST) ACGIH TLV:5MG/CUM (DUST)

Ingred Name:IRON ION (FE +2) CAS:15438-31-0 RTECS #:NO6925000 Fraction by Wt: 30%PPM OSHA PEL:1 MG/M3 (FE) ACGIH TLV:1 MG/M3 (FE); 8990

Ingred Name:WATER SOLUBLES Fraction by Wt: 0.1%

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES Health Hazards Acute and Chronic: ACUTE: MAY CAUSE SEVERE IRRITATION OF EYES, SKIN AND RESPIRATORY TRACT. AVOID DUSTY SITUATIONS. CHRONIC: NOT KNOWN. MAY HAVE RESPIRATORY ALLERGIC REACTIONS. Effects of Overexposure: SKIN: MAY CAUSE SEVERE IRRITATION OR INJURY. EYES: MAY CAUSE SEVERE IRRITATION OR INJURY. INHALATION: **RESPIATORY IRRITATION OR SOME ALLERGIC REACTIONS. INGESTION: IRRITATION TO MUCOUS MEMBRANES**, NAUSEA, VOMITING. Medical Cond Aggravated by Exposure:NO DATA AVAILABLE. First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED; EYES/SKIN: FLUSH W LG AMTS H*20 FOR 15 MIN; INGEST: RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYM PTOMS OF OVEREXPOSURE. Flash Point:NONE Extinguishing Media: NO SPECIAL REQUIREMENT. IN CASE OF SURROUNDING FIRE, USE FOAM, CO*2, WATERFOG. Fire Fighting Procedures: USE SCBA IN AN ENCLOSED AREA (NIOSH/MSHA APPROVED). Unusual Fire/Explosion Hazard: AT 1112F (600C) SODIUM SULFIDE IS FORMED AT 1652F(900C)SO*2 IS FORMED. USE SCBA FOR FIRE FIGHTING

Spil

I Release Procedures: CONTAIN ALL SPILLED MATERIAL. DO NOT FLUSH TO SURFACE WATERS. COLLECT DRY MATERIALS IN SUITABLE CONTAINERS.

Handling and Storage Precautions:PROTECT CONTAINERS FROM DAMAGE.STORE IN DRY AREA AWAY FROM ACIDS,AND OXIDIZING AGENTS. Other Precautions:DO NOT INHALE DUST. AVOID SKIN AND EYE EXPOSURE.

Respiratory Protection:DUST MASK/DUS T RESPIR Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN