

STEVEN INDUSTRIES, NORTECH CORP -- NITRILE/RESIN -- 8040-00-266-0824

=====
Product Identification
=====

Product ID:NITRILE/RESIN

MSDS Date:01/01/1987

FSC:8040

NIIN:00-266-0824

MSDS Number: BDRGJ

=== Responsible Party ===

Company Name:STEVEN INDUSTRIES, NORTECH CORP

Emergency Phone Num:201-653-8647

CAGE:DO669

=== Contractor Identification ===

Company Name:STEVEN INDUSTRIES, INC

Address:39 AVENUE C

/ PO BOX 8

Box:8

City:BAYONNE

State:NJ

ZIP:07002

Phone:201-437-6500

CAGE:DO669

Company Name:STEVEN K L CO

Address:300-B INDUSTRIAL DR

Box:15155

City:RIO RANCHO

State:NM

ZIP:87174-3545

Country:US

CAGE:56800

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

Fraction by Wt: 70.0%

ACGIH TLV:10PPM

Ingred Name:POLYMERS

Fraction by Wt: 30.0%

=====
Hazards Identification
=====

Effects of Overexposure:EYE/THROAT/SKIN/LUNG IRR

IT

=====
First Aid Measures
=====

First Aid:WASH SKIN THOROUGHLY, FLUSH EYES W/WATER, REMOVE TO FRESH AIR, REMOVE CONTAM CLOTHING. GIVE ARTIF RESP IF NEEDED, CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:20F-6.7C
Lower Limits:1.80
Upper Limits:1.50
Extinguishing Media:FOAM, DRY CHEM, FOG, CARBON DIOXIDE
Fire Fighting Procedures:AS VERY FLAMMABLE LIQ
Unusual Fire/Explosion Hazard:AVOID FIRE, HEAT, SPARKS, IG
NIT SOURCES,
STG IN DIRECT SUNLIGHT

=====
Accidental Release Measures
=====

Spill Release Procedures:VENT AREA MECH, KEEP FROM FLAME, FIRE SPARKS, IGNIT SOURCES. DO NOT BREATHE VAPORS. CLEAN UP W/ABSORBENT MATL.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CNTNRS CLOSED, UPRIGHT, AWAY FROM FIRE, FLAME SPARKS, IGNITION SOURCES, DIRECT SUNLIGHT.

=====
Exposure Controls/Personal Protec
tion
=====

Respiratory Protection:RESP APPRVD FOR ORGANIC SOLVENT
Ventilation:LOCAL EXHST
Protective Gloves:GLOVES
Eye Protection:GOGGLES/GLASSES
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:132F-55.6C
Vapor Pres:186
Spec Gravity:0.7000
Evaporation Rate & Reference:5.0 BUAC
Solubility in Water:NONE
Appearance and Odor:YELLOW COLORED LIQ
Percent Volatiles by Volume:75.0

=====
Stability
=====

and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.