View NSN Online: https://aerobasegroup.de/nsn/6750-00-266-7627

EASTMAN KODAK COMPANY -- 146 4932 DK-50 DEVELOPER,PART A -- 6750-00-266-7627

Product ID:146 4932 DK-50 DEVELOPER, PART A MSDS Date:05/31/1995 FSC:6750 NIIN:00-266-7627 Kit Part:Y MSDS Number: BDRHN === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

Ingred Name

:HYDROQUINONE (SARA 302/313) (CERCLA) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 50% Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9495 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:P-METHYLAMINOPHENOL SULFATE (METOL) CAS:55-55-1 RTECS #:SL8650000 Fraction by Wt: 45 - 50% Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture: TLV FOR HYDROQUINONE IS 2 MG/M3. Routes of Entry: Inhalation:YES Skin:NO Inge stion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYES, SKIN, RESPIRATORY AND GASTROINTESTINAL TRACTS. ACUTE- CAUTION. CONTAINS HYDROQUINONE. INHALE:MAY CAUSE IRRITATION. HARMFUL IF INHALED. EYES/SKIN:CAUSES IRRITATION. MAY CAUSE ALLERG IC SKIN REACTION. ORAL: HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF GI TRACT. CHRONIC- MAY CAUSE EYE INJURY. Explanation of Carcinogenicity:NONE Effects of Overexposure: IRRITATION, AL LERGIC SKIN REACTION, EYE INJURY, PAIN Medical Cond Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. INHALED:REMOVE TO FRESH

AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL: IF CONSCIOUS, INDUCE VOMITING IMMEDIATELY AS DIRECTED BY MEDICAL PERSONNEL. CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING TO AN UNCONSCIOUS PERSON.

Flash Point:NONE
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. USE
WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOS
H-APPROVED
SELF-CONTAINED BREATHING APPARATUS. FIRE MAY PRODUCE HAZARDOUS

DECOMPOSITION PRODUCT. Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST- AIR MIXTURES.

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT. VACUUM SPILLAGE WITH A VACUUM CLEANER OR CAREFULLY SWEEP UP. AVOID RAISING DUST. WASH SPILL SITE AFTER PICK-UP IS COMPLETE. Neutralizing Agent:NOT RELEVANT

=======

Handling and Storage Precautions: KEEP CONTAINER CLOSED. STORE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions: AVOID CONTACT WITH EYES, SKIN AND CLOTHING. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. THE ROUTINE USE OF A NONALKALINE (ACID) TYPE OF HAND CLEANER AND REGULAR CLEANING OF WORKING SURFACES WILL MINIMIZE SKIN REACTION.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS TO AN ACCETABLE LEVEL, A NIOSH-APPROVED RESPIRATOR FOR DUST MUST BE WORN. IF RESPIRATORS ARE USED, A PROGRAM SHOULD BE INSTITUTED TO ASS URE COMPLIANCE WITH OSHA 29CFR 1910.134.
Ventilation: GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. TYPICALLY, 10 ROOM VOLUMES PER HR IS CONSIDERED GOOD GENERAL VENTILATION.
Protective Gloves: RUBBER/LATEX
Eye Protection: SAFETY GLASSES WITH SIDE SHIELD/GOGGLES Other Protective Equipment: EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

KEY1:T4. SEE PNI B FOR PART B. THIS PRODUCT HAS: A HIGH BIOCHEMICAL OXYGEN DEMAND, A HIGH POTENTIAL TO AFFECT AQUATIC ORGANISMS. AFTER DILUTION WITH A LARGE AMOUNT OF WATER, FOLLOWED BY WASTE TREATMEN T, IT IS NOT EXP ECTED TO CAUSE ADVERSE ENVIRONMENT EFFECTS.

HCC:T4 NRC/State Lic Num:NOT RELEVANT Vapor Pres:NEGLIGIBLE Spec Gravity:1.00 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:COMPLETE Appearance and Odor:LIGHT TAN SOLID - ODORLESS Percent Volatiles by Volume:NEGLIG

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZI NG AGENTS Stability Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF SULFUR, OXIDES OF NITROGEN MAY BE FORMED.

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS. CONTRACT WITH A LICENSED CHEMICAL DISPOSAL AGENCY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.