

J.C.ENTERPRISES -- ENTERPRISE 1000;LUBRICATING OIL WATCH -- 9150-00-270-0063

=====
Product Identification
=====

Product ID:ENTERPRISE 1000;LUBRICATING OIL WATCH

MSDS Date:01/01/1987

FSC:9150

NIIN:00-270-0063

MSDS Number: BDRNK

=== Responsible Party ===

Company Name:J.C.ENTERPRISES

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

ZIP:19803-1712

Info Phone Num:302-478-8326

Emergency Phone Num:302-

478-8326

CAGE:LO045

=== Contractor Identification ===

Company Name:J C ENTERPRISES INC

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Phone:302-478-8326

CAGE:2S598

Company Name:J.C.ENTERPRISES

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

ZIP:19803-1712

Phone:302-478-8326

CAGE:LO045

=====
Composition/Information on Ingredients
=====

Ingred Name:BENZYL PHENYLUNDECANOATE

Fraction by Wt: 59.95%

Ingred Name:DIETHYLENE GLYCOL DI-N-CAPROAT

E

Fraction by Wt: 39.45%

Ingred Name:DODECYLPIPERIDINE STEARATE

Fraction by Wt: 0.40%

Ingred Name:P-TERTIARY-BUTYL CATECHOL

Fraction by Wt: 0.20%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:MAY IRRITATE EYES & SKIN;NO
OTHER DATA GIVEN. CHRONIC:NO DATA AVAILABLE.
Effects of Overexposure:EYE: IRRITATES
Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH OUT W/WATER; GET MEDICAL ATTENTION IMMEDIATELY;
INHALATION: NONE; INGESTION NONE IDENTIFIED

=====
===== Fire Fighting Measures =====

Flash Point:>392F/200C
Extinguishing Media:DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE WHEN USED AS A LUBRICATING OIL FOR
INSTRUMENTS,JEWEL BEARING,NON-SPREADING APPLICATION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN LIQUID,COVER WITH OIL DRY
COMPOUND,SWEEP-UP

=====
===== Handling and Storage =====

Handling and Storage Precautions:USE NORMAL TECHNIQUES FOR HANDLING
ORGANIC CHEMICALS WHICH ARE USED AS LUBRICATING OILS. LONG TERM
STORAGE IN SUNLIGHT WILL CAUSE COLOR CHANGE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:NORM

AL ROOM VENTILATION.

Protective Gloves:NONE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

MSDS FROM JC ENTERPRISES INC NOT DATED. SPEC REF: MIL-L-3918A

===== Physical/Chemical Properties =====

HCC:V6

Solubility in Water:NEGLIGIBLE

Appearance and Odor:STRAW TO GOLDEN YELLOW; MILD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials t

o Avoid:YES

NONE

Stability Condition to Avoid:AVOID IGNITION SOURCES

Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE, OR BURY BUT DISPOSAL METHOD SHOULD BE IN COMPLIANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The Unite

d States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.