View NSN Online: https://aerobasegroup.de/nsn/9150-00-271-8427 SOUTHWEST PETRO-CHEM -- SF 871 1010 -- 9150-00-271-8427 ============= Product Identification ======================== Product ID:SF 871 1010 MSDS Date:01/01/1987 FSC:9150 NIIN:00-271-8427 MSDS Number: BDRWY === Responsible Party === Company Name: SOUTHWEST PETRO-CHEM Emergency Phone Num: (913) 782-5800 CAGE:70878 === Contractor Identification === Company Name: EXXON CO USA-SOUTHWEST GREASE BUSINESS UNIT Address:1400 S HARRISON Box:1974 City:OLATHE State:KS ZIP:66061 Country:US Phone:913-656-3701/800-424-9300(CHEMTREC) CAGE:70878 ======= Composition/Information on Ingredients ======== Ingred Name: MINERAL OIL; CAS #64742-52-5 CAS:64742-52-5 RTECS #:PY8035000 ACGIH TLV:5MG/CUM(MIST) Ingred Name:BARIUM SULFONATE; CAS #61790-48-5 Ingred Name: THICKENING AGENT ========== Hazards Identification ================= Effects of Overexposure: EYES: IRRITATION; SKIN: IRRITATION ON

PROLONGED/REPEA

| TED CONTACT;INGEST:NAUSEA,HEAD,GI IRRITATION,DIARR |
|---|
| ====================================== |
| First Aid:SKIN:WASH W.SOAP & H*20 EYES:FLUSH W. H*20. INGESTED:GIVE 2 GLASSES H*20; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHING BY MOUTH. |
| ====================================== |
| Flash Point:334F/168C (COC) Extin guishing Media:CO*2, FOAM, DRY CHEM & H*20 FOG. Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR. |
| Unusual Fire/Explosion Hazard:BURNS WITH DENSE SMOKE. |
| ========= Accidental Release Measures ========== |
| Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AU THORITIES. |
| ========== Handling and Storage =========== |
| Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED Other Precautions:AVOID CONTACT WITH SKIN,EYES & CLOTHING.WASH THOROUGHLY AFTER HANDLING.KEEP AWAY FROM FEED & FOOD PRODUCTS.LAUNDER CLOTHES BEFORE REUSE. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Prote ction:NONE SHOULD BE NEEDED Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT. Protective Gloves:RUBBER/PLASTIC Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS. Supplemental Safety and Health MSDS FM MFR DATE:9/5/85; SPEC REFERENCE: MIL-L-3150C. |
| ========= Physical/Chemical Properties ========== |
| HCC:V6 Spec Gravity:0.926 Solubility in Water:NEGLIGIBLE Appearance and Odor:AMBER COLOR OIL.MINERAL OIL ODOR. |
| ======================================= |

| Stability Indicator/Materials to Avoid:YES |
|---|
| STRONG OXIDIZING AGENTS. |
| Stability Condition to Avoid: EXCESSIVE HEAT & IGNITION SOURCES |
| Hazardous Decomposition Products: INCOMPLETELY BURNED CARBON PRODUCTS |

======= Disposal Considerations =============

==== Stability and Reactivity Data =========

CO*2, CO.

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & L OCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.