View NSN Online: https://aerobasegroup.de/nsn/6810-00-281-2764

Product ID:BENZENE AR MSDS Date:01/01/1987 FSC:6810 NIIN:00-281-2764 MSDS Number: BDSVZ === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION Address: PARIS BYPASS Box:M City:PARIS State:KY ZIP:40361 Country:US Info Phone Num:314-982-5000 **Emergency Phone Num:** 314-982-5000 CAGE:62910 === Contractor Identification === Company Name: MALLINCKRODT SPECIALTY CHEMICALS CO Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:908-859-2151 CAGE:62910 Ingred Name: BENZENE (SARA III) CAS:71-43-2 RTECS #:CY1400000 Fraction by Wt: >99% OSHA PEL:1PPM/5STEL;1910.1028 ACGIH TLV:10 PPM; A2; 9192 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS ========================= Hazards Id

Effects of Overexposure:INH:MAY BE FATAL.MAY CAUSE DIZZ,HEAD,LVR/KDNY DAMG;ING:SAME AS INH;SKIN/EYES:IRRITANT.MAY CAUSE PAIN

First Aid:INHAL:RMV TO FRESH AIR. IF NEEDED,GIVE CPR/OXYGEN.GET MD;INGEST:GIVE SEVRL GL OF WATER.DO NOT INDUCE VOMITG.IMMED GET MD;SKIN:FLUSH W/LG QTY OF H*20 FOR 15 MIN.REMV CONTMNTD CLOTHES.GET MD;EYES;IMMED FLUSH W/PLENTY OF H*20 FOR AT LEAST 15 M IN.GET MD.

Flash Point:-11C(12F)-C.C Lower Limits:1.0 Upper Limits:8.0 Extinguishing Media:DRY POWDER, FOAM, CARBON DIOXIDE Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR. Unusual Fire/Explosion Hazard:EXPLOSIVE VAPOR/AIR MIXTURES MAY FORM

ABOVE FLASH POINT.CONTAINER MAY EXPLODE IN HEAT OR FLAME.

Spill Release Procedures:

VENTILATE & EVAC AREA.USE PROTCTV CLOTHG &

RESP PROTCTION FM VAP.CONTAIN & RECOVR LIQ WHEN POSS.SPILLS MAY BE ABSORBD W/SAND,VERMICULITE OR OTHER INERT MATL & CONTAINERIZE FOR DISPOSAL.USE H*20 SPRAY TO DISPRS VAPS,TO FLUSH AWAY/DILUTE SPILLS.RMV IGN

Handling and Storage Precautions: KEEP IN TIGHTLY CLOSED CONTNRS AT COOL, DRY, VENTILATED PLACE. PROTECT AGAINST PHY DAMAGE. OUTSIDE OR DETACHED STORAGE IS PRE FERRED. KEEP AWAY FM OXIDIZERS

Other Precautions: AVOID BREATHING DUST. USE W/ADEQUATE VENTILATION. KEEP CONTAINRS CLOSED. WASH THOROUGHLY AFTER HANDLING. AVOID SKIN, EYES & CLOTHING CONTACT; CANCER HAZRD; OVEREXPOSURE MAY CREATE CANCER RISK.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:SUPPLIED AIR RESPIR/SCBA; ESCAPE: GAS MASK Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS Eye Protection:GOGGLES/FACE SHIELD Other Prot HCC:F2 Boiling Pt:B.P. Text:80C(176F) Vapor Pres:100 Vapor Density:2.7 Spec Gravity:0.88 Evaporation Rate & amp; Reference:2.8(ETHER=1) Solubility in Water:NEGLIGI BLE Appearance and Odor:CLEAR COLORLESS LIQ;SWEET AROMATIC ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES OXIDIZERS,CORROSIVE MATL(CLF*3,H*2SO*4,K,CHROMIC ANHYDRIDE) Stability Condition to Avoid:IGNITION SOURCES Hazardous Decomposition Products:TOXIC GASES & VAPOR SUCH AS CARBON MONOXIDE

Waste Disposal Methods:WASTE CAN BE ATOMIZED IN A CHEMICAL INCINERATOR

SUITABLE FOR BURNING HAZARDOUS WASTE & EQUIPPED W/AN AFTERBURNER & SCRUBBER SYSTEM.ENSURE COMPLIANCE W/LOCAL,STATE & FED REGS. CWA/CERCLA RQ: 1000LBS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabi

lity for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.