

NON FLUID OIL CORPORATION -- CHEM-PLEX 1381 -- 6850-00-281-4033

===== Product Identification =====

Product ID:CHEM-PLEX 1381

MSDS Date:01/01/1987

FSC:6850

NIIN:00-281-4033

MSDS Number: BDSYP

=== Responsible Party ===

Company Name:NON FLUID OIL CORPORATION

Emergency Phone Num:(201)344-3451

CAGE:LO133

=== Contractor Identification ===

Company Name:NON FLUID OIL CORPORATION

CAGE:LO133

Company Name:N

ONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYL POLY SILOXANE (TLV AS OIL MIST)

Fraction by Wt: U/K

ACGIH TLV:5MG/CUM

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

Fraction by Wt: U/K

OSHA PEL:15MG/M3 TDUST/5 FUME

ACGIH TLV:10MG/M3 TDUST; 9293

===== Hazards Identifi

caution =====

Effects of Overexposure:MAY CAUSE TEMPORARY DISCOMFORT TO EYES;OR SKIN ON PROLONGED CONTACT.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Po
int:500F/260 (C OC)
Lower Limits:U/K
Upper Limits:U/K
Extinguishing Media:CO*2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:USE NIOSH APPROVED SCBA IN FIRES AND CONFINED AREA
Unusual Fire/Explosion Hazard:NONE SPECIFIED.USE REASONABLE CARE.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION.USE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

===== Handling and Storage =====

H
Handling and Storage Precautions:STORE IN COOL DRY AND VENTILATED AREA.KEEP AWAY FROM HEAT AND OPEN FLAMES.KEEP CONTAINER TIGHTLY CLOSED
Other Precautions:AVOID SKIN AND EYE CONTACT.DO NOT USE CONTAMINATED CLOTHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR FOR OIL MIST IF CREATED.
Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 300F/149C
Vapor Pres: