View NSN Online: https://aerobasegroup.de/nsn/6810-00-281-6928

UNION CHEM DIV,UNION OIL CO,MXR;PHIPPS PROD,DIST -- AMSCO SOLV 5305 -- 6810-00-281-6928

Product ID:AMSCO SOLV 5305

MSDS Date:01/01/1985

FSC:6810

NIIN:00-281-6928

MSDS Number: BDTBQ === Responsible Party ===

Company Name: UNION CHEM DIV, UNION OIL CO, MXR; PHIPPS PROD, DIST

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

State:IL ZIP:60195 Country:US

Info Phone Num:312-619

-2644

Emergency Phone Num:312-619-2644

CAGE:LO137

=== Contractor Identification ===

Company Name: UNION CHEM DIV, UNION OIL CO, MXR; PHIPPS PROD, DIST

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

State:IL ZIP:60195 Country:US

Phone:312-619-2644

CAGE:LO137

Company Name: UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL ZIP:60195 Country:US

Phone:708-619-2644

CAGE:77416

======= Composition/Information on Ingredients ========

Ingred Name:

Fraction by Wt: 100% OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
======================================
Effects of Overexposure:EYES:IRRITATS.SKIN:PROLONGED CONTACT IRRITATS;MAY PRODUCE DERMM.HAUS,VOMIT,CNS DEPRESS,RESPIR IRRIT.
======================================
First Aid:SKIN:WASH W.SOAP & H*20 EYES:FLUSH W. H*20. INGESTED: GIVE 2
GLASSES H*2O; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHINGBY MOUTH.
======================================
Flash Point:75F/23.8C CC
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:KEEP WOR
K AREAS FREE OF HOT METAL
SURFACES AND OTHER SOURCES OF IGNITION.
======== Accidental Release Measures =========
Spill Release Procedures:DO NOT TOUCH SPILL MATL. SM SPILL:ABSORB W SAND,OTHER NON COMBUSTIBLES ABSORB; FLUSH W/H*20 LG SPILL:DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL ELIMINATE IGNITION SOURCES.AVOID HOT METAL SURFACES.
=========== Handling and Storage =============
Handling and Storage Precautions:STORE IN COOL,DRY,WELL

N-BUTYL ALCOHOL (SARA III) CAS:71-36-3

RTECS #:EO1400000

VENT, LOW FIRE

RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID INHALATION OF VAPOR & PERSONAL CONTACT.IF CONTACT,REMOVE SATURATED CLOTHING AND FLUSH EXPOSED AREA WITH WATER.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:IF EXCEED TLV,USE NIOSH APPRVD CARTRIDGE RESPIR OR GAS MASK.

Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED

Protecti

ve Gloves:IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment:FACE SHIELDS,IMPERMEABLE APRONS;EYE

WASH, SAFETY SHOWERS. Supplemental Safety and Health

MSDS EFFECTIVE:10/21/80.CHEMTREC EMERGENCY

TELEPHONE:800-424-9300;POISON CONTROL:213-664-2121.

======== Physical/Chemical Properties ===========

HCC:F3

Boiling Pt:=117.8C, 244.F

Vapor Pres:UNK Vapor Density:>1 Spec Gravity:0.74

Evaporation Rate & Dr. Reference: