

OCTAGON PROCESS,INC. -- O-C-265 CHEMICAL ANALYTICAL, GEN. SPEC. FOR -- 6810-00-281-9827
===== Product Identification =====

Product ID:O-C-265 CHEMICAL ANALYTICAL, GEN. SPEC. FOR

MSDS Date:01/01/1985

FSC:6810

NIIN:00-281-9827

MSDS Number: BDTFK

=== Responsible Party ===

Company Name:OCTAGON PROCESS,INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945-

9400

Emergency Phone Num:201-945-9400

CAGE:DO973

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

Company Name:OCTAGON PROCESS,INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Phone:201-945-9400

CAGE:DO973

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT21000

00

= Wt:85.

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:BURNS ON ALL BODY TISSUE,CONJUNCTIVITIS,
IRRITATION OF RESPIRATORY TRACT,INFLAMMATION OF LUNGS,NAUSEA

===== First Aid Measures =====

First Aid:IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15
MINUTES & GET MEDICAL ATTENTION.WASH CONTAMINATED AREA
S OF BODY
WITH SOAP & WATER.TREAT SKIN BURNS AS USUAL.STOMACH WASH,IF
SWALLOWED, WITH 5 PERCENT ACETIC ACID,FOLLOWED BY INSTILL OF
OLIVES

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE LARGE VOLUME OF WATER,BUT DO NOT SPLASH ITS
SOLUTION

Unusual Fire/Explosion Hazard:MODERATE FIRE HAZARD,GENERATES HEAT WHEN
MIXED WITH WATER,OR STEAM;CONTACT WITH METALS EVOLVE H2.

===== Accidental Release Measures

=====

Spill Release Procedures:NEUTRALIZE WITH 5 PERCENT ACETIC ACID.FLUSH
WITH ABUNDANCE OF WATER.CAUTION:AVOID SPATTERING WHEN WATER IS
ADDED

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PLACE TO PREVENT
CORROSION OF THE SURFACE OF DRUM,ABSORPTION OF
MOISTURE,FREEZING,ETC;WEAR RUBBER GLOVES, FACE SHIELD & WORKING
CLOTHES.

Other Precautions:STORE AWAY FROM FLAMMABLE & OXIDIZING MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:U.S.BUREAU OF MINES DUST MASK REQUIRED.
Ventilation:AS REQUIRED TO CONTROL TLV IN AIR.
Protective Gloves:RUBBER
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:LARGE FACE SHIELD & PROTECTIVE CLOTHING
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:B1
Boiling Pt.=1320.C, 2408.F
Solubility in Water:APPRECIABLE
Appearance and Odor:WHITE DELI
QUESCENT PIECES.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIALS,ACIDS,METALS,EXPLOSIVES,ORGANIC PEROXIDE
Stability Condition to Avoid:HEAT

===== Disposal Considerations =====

Waste Disposal Methods:PUT INTO LARGE VESSEL CONTAINING
WATER.NEUTRALIZE WITH HCL. DISCHARGE INTO APPROVED DISPOSAL AREA
WITH SUFFICIENT WATER

Disclaimer (provided with this information by the co
mpiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.