

ASHLAND OIL CO. -- TECTYL 437 -- 8030-00-285-1570

=====
Product Identification
=====

Product ID:TECTYL 437
MSDS Date:01/01/1987
FSC:8030
NIIN:00-285-1570
MSDS Number: BDTLP
=== Responsible Party ===
Company Name:ASHLAND OIL CO.
Emergency Phone Num:614-790-3333
CAGE:81355
=== Contractor Identification ===
Company Name:ASHLAND INC
Address:1409 WINCHESTER AVE
Box:391
City:ASHLAND
State:KY
ZIP:41114
Country:US
Phone:800-622-6846
CAGE:81355

=====
Composition/Information on Ingredients
=====

Ingred Name:2000 PALE OIL
Fraction by Wt: 60%
ACGIH TLV:5 MG/CUM

=====
Hazards Identification
=====

Effects of Overexposure:BREATHING:EXCESS INHAL OF VAP CAN CAUSE NASAL &
RESPIR IRRITAT DIZZINESS,WEAKNESS,FATIGUE,NAUSEA(SUP

=====
First Aid Measures
=====

First Aid:BREATHED-IF AFFECTED,REMOVE INDIV TO FRESH
AIR.BREATHING
DIFFICULT,ADMINISTER OXYGEN,IF STOPPED,GIVE ARTIFICIAL
RESPIRAT.KEEP PERSON WARM,QUIET & GET MEDICAL ATTN.SWALLOWED: 2
GLASS OF WATER,INDUCE VO MIT IMMED BY STICKING FINGER DOWN
THROAT.CALL DR.

=====
Fire Fighting Measures
=====

Flash Point:460F 238C
Extinguishing Media:DRY CHEM,CARBON DIOXIDE
Fire Fighting Procedures:WATER OR FOAM MAY CAUSE FROTHING WHICH CAN BE
VIOLENT(SE SUP

=====
Accidental Release Measures
=====

=====

Spill Release Procedures:SMALL SPILL-ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL & TRANSFER TO HOOD.LG SPILL-PERSONS NOT WEARING PROTECTIVE EQUIPMT SHD BE EXCLUDED FR AREA OF SPILL UNTIL CLE AN-UP HAS BEEN COMPLETED.STOP SPILL AT SOURCE.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED.SINCE EMPTIES CONTAINERS RETAIN PRODUCT RESIDUE ALL HAZ PRECAUTIONS GIVEN MUST BE OBSERVED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV OF PRODUCT OF ANY COMPON EXCEEDED,USE APPRVD SELF-CONTAIN BRE
Ventilation:PROVIDE SUFFICIENT MECH/LOC EXHAUST VENTIL TO KP BELOW TLV
Protective Gloves:NEOPRENE
Eye Protection:WEAR SAFETY GLASSES
Other Protective Equipment:TO PREVENT RPTD OR PRLNGED SKN CONTACT,WEAR IMPERV CLOTH/BOD
Supplemental Safety and Health
FIRE F
IGHT:& POSSIBLY ENDANGER LIFE OF FIREFIGHTER.SELF-CONTAINED BREATHING APPARAT W/A FULL FACEPIECE OPERATED IN PRESSR-DEMD OR OTHER POSITVE PRESR MOD EXPOS:POSS UNCONSCIOUSNESS & EVEN ASPH

===== Physical/Chemical Properties =====

HCC:N1
Spec Gravity: