View NSN Online: https://aerobasegroup.de/nsn/9160-00-285-2045

US WAX INC. -- PETROLEUM WAX:USW#135-140 -- 9160-00-285-2045

Product ID:PETROLEUM WAX:USW#135-140 MSDS Date:01/01/1987 FSC:9160 NIIN:00-285-2045 MSDS Number: BDTLZ === Responsible Party === Company Name: US WAX INC. Emergency Phone Num:215-757-3740 CAGE:LO157 === Contractor Identification === Company Name: US WAX INC Address:618 N WOODBOURNE RD Box:City:LANGHORNE State:PA ZIP:19047 Country:US CAGE:4W679 Company Name: US WAX INC. CAGE:LO157

Ingred Name:PETROLEUM WAX BLEND (PER MFR,TAKE TLV AS OIL MIST =5MG/CUM) Fraction by Wt: 100%

Effects of Overexposure:EYES:MILD IRRIT;SKIN:WILL SOFTEN CALLOUSED SKIN;INHAL:RESP.TRACT IRRIT.INGEST:MAY ACT AS LAXATIVE.

=======

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

Flash Point:>400F/204C Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATERFOG Fire Fighting Procedures:TREAT AS OIL FIRE;USE NIOSH/MSHA APPROVED SCBA IN CONFINED A Unusual Fire/Explosion Hazard:PR ODUCTS OF COMBUSTION-SMOKE, CO & CO*2

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; SCRAPE UP MATERIAL INTO WASTE CONTAINERS. CLEAN THE AREA WITH DETERGENT.

 Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM HEAT,OPEN FLAME & OXIDIZING MATERIALS.
 Other Precautions:AVOID PERSONAL CONTACT;WASH WITH SOAP AND WATER AFTER EA

CH USE.DO NOT SMOKE, EAT OR DRINK IN WORK AREA.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORG.VAPORS/MIST IF ABOVE TLV.
Ventilation: MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION
Protective Gloves: IMPERVIOUS
Eye Protection: CHEM SPLASH GOGGLES
Other Protective Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.
Supplemental Safety and Health
MSDS DATED:NIL; PLANT LO CATION PHONE #609-695-6771

HCC:N1 Vapor Pres:NIL Spec Gravity:0.8035 Evaporation Rate & amp; Reference:0.0 (ETHYL ETHER=1 Solubility in Water:NEGLIGIBLE Appearance and Odor:WHITE WAX (SOLID AT ROOM TEMP.)ODORLESS Percent Volatiles by Volume:0.0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:EXTREME HEAT,OPEN F

LAME

Hazardous Decomposition Products:NONE NOTED BY MFR.PROD OF COMBUSTION:CO AND CO*2 OR SMOKE

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expre

ssly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.