

AMERON PROTECTIVE COATINGS -- GREY 16187 -- 8010-00-286-7731

=====
Product Identification
=====

Product ID:GREY 16187
MSDS Date:01/01/1987
FSC:8010
NIIN:00-286-7731
MSDS Number: BDTWV
=== Responsible Party ===
Company Name:AMERON PROTECTIVE COATINGS
Address:201 NORTH BERRY STREET
City:BREA
State:CA
ZIP:92622-1020
Country:US
Info Phone Num:714-529-1951
Emergency Phone Num:714-529-1951
CAGE:0Y2E4

==
= Contractor Identification ===
Company Name:AMERON PROTECTIVE COATINGS
Address:201 NORTH BERRY STREET
Box:1020
City:BREA
State:CA
ZIP:92622-1020
Country:US
Phone:714-529-1951
CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 44.1%
Other REC Limits:STEL 400 PPM
OSHA PEL:100 PPM
ACGIH TLV:300 PPM

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITATION OF
RESPIRATORY TRACT & NERVOUS SYSTEM DEPRESSION. SKIN/EYES:
IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION

===== First Aid Measures =====

First Aid:SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:85F
Lower Limits:1.1
Extinguishing Media:SMALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR
FIREMEN.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING
VAPORS. REMOVE W/INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQUID TO EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOS

H APPROVED PAINT RESPIRATOR/AIR SUPPLIED
RESPIRATOR. RESPIRATOR USED BASED ON CHEMICAL CONDITION &
CONDITIONS OF USE.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST AS NECESSARY.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Vo

lume:60.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRE, HEAT, HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL,STATE AND FEDERAL
REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of t

he Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.