

CON-LUX COATINGS INC -- ENAMEL,ALKYD,GLOSS 16187 -- 8010-00-286-7731

=====
Product Identification
=====

Product ID:ENAMEL,ALKYD,GLOSS 16187
MSDS Date:01/01/1985
FSC:8010
NIIN:00-286-7731
MSDS Number: BDTWW
=== Responsible Party ===
Company Name:CON-LUX COATINGS INC
Address:226 TALMADGE RD
Box:847
City:EDISON
State:NJ
ZIP:08818-0847
Country:US
Info Phone Num:908-287-4000 / FAX 908-287-9288
Emergenc
y Phone Num:908-287-4000
CAGE:60189
=== Contractor Identification ===
Company Name:CON-LUX COATINGS INC
Address:226 TALMADGE RD
Box:847
City:EDISON
State:NJ
ZIP:08818-0847
Country:US
Phone:732-287-4000
CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 43.9%
OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TL

=====
Hazards Identification
=====

Effects of Overexposure:IRRITATION OF EYES AND SKIN. IRRITATION OF RESPIRATORY TRACT. HEADACHE OR DIZZINESS.

=====
First Aid Measures
=====

First Aid:SKIN/EYES:FLUSH WITH WATER.INHAL:MOVE TO FRESH AIR.IF IRRITATION PERSISTS,CALL DR.

=====
Fire Fighting Measures
=====

Flash Point:40.6/105

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CLASS B EXTINGUISHERS (CO*2, DRY CHEM.OR FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND ISOLATE FROM SOURCES OF IGNITION.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT SURFACES,ELECTRICAL,STATIC OR FRICTIONAL SPARKS)AVOID BREATHING OF VAPORS. VENTILATE AREA. REMOVE WITH NON-SPARKING TOOLS AND INERT ABSORBENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP.KEEP AWAY FROM OPEN FLAMES AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM/MECH FILTER

RESPIRATOR

Ventilation:LOCAL EXHAUST

Protective Gloves:YES

Eye Protection:SAFETY GLGGLES OR GLASSES

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING

Supplemental Safety and Health

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY
TO HOT SURFACES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:157.2/315

Vapor Pres:1

Vapor Density:4.7

Spec Gravity:1.04

Evaporation Rate & Reference:BUA

C=1:0.15

Solubility in Water:0

Appearance and Odor:GRAY LIQUID,MILD ALIPHATIC ODOR

Percent Volatiles by Volume:59.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:DOSPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with th

is information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.