

AMERON PROTECTIVE COATINGS -- YELLOW 13538 -- 8010-00-286-7758

=====
Product Identification
=====

Product ID:YELLOW 13538

MSDS Date:01/01/1985

FSC:8010

NIIN:00-286-7758

MSDS Number: BDTXQ

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

City:BREA

State:CA

ZIP:92622-1020

Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2

E4

=== Contractor Identification ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 38.0%

Other REC Limits:STEL 400 PPM

OSHA PEL:100 PPM

ACGIH TLV:300 PPM

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE
Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A
PHYSICI
AN IF CONDITIONS PERSIST.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:85F
Lower Limits:1.1
Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE
FIRES-FOAM
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES
OF IGNITION. AVOID
BREATHING VAPORS. REMOVE WITH INET ABSORBENT AND NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.