

ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC -- AIR CARBON ARC ELECTRODE --
3439-00-288-4048

===== Product Identification =====

Product ID: AIR CARBON ARC ELECTRODE

MSDS Date: 10/31/1990

FSC: 3439

NIIN: 00-288-4048

MSDS Number: BDTZY

=== Responsible Party ===

Company Name: ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC

Address: 4200 WEST HARRY ST

Box: 12250

City: WICHITA

State: KS

ZIP: 67277

Country: US

Info Phone Num: 316-942-1421

Emergency Phone Num: 316-942-1421

Preparer's Name: DENNIS WILSON

CAGE: 09687

=== Contractor Identification ===

Company Name: ARCAIR CO SUB OF AIR PRODUCTS AND CHEMICALS INC

Address: 4200 WEST HARRY ST

Box: 12250

City: WICHITA

State: KS

ZIP: 67277

Country: US

Phone: 316-942-1421

CAGE: 09687

Company Name: SMITH S J CO INC

Address: 3707 W RIVER DR

Box: City: DAVENPORT

State: IA

ZIP: 52802-2411

Country: US

Phone: 319-324-5237

CAGE: 2N560

Company Name: TWECO PRODUCTS, INC.

Address: 4200 WEST HAR

RY ST.
Box:12250
City:WICHITA
State:KS
ZIP:67277
Country:US
Phone:316-946-8308;316-942-1421
CAGE:89381

===== Composition/Information on Ingredients =====

Ingred Name:GRAPHITE, SYNTHETIC *
CAS:7440-44-0
RTECS #:FF5250100
Fraction by Wt: 20-90%
OSHA PEL:3.5 MG/M3 (MFR)
ACGIH TLV:2 MG/M3 TDUST; 9192

Ingred Name:GRAPHITE, NATURAL *
CAS:7782-42-5
RTECS #:MD9659600
Fraction by Wt: 20-90%
OSHA PEL:2.5 MG/M3 RDUST *
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:COPPER (SARA III) *
CAS:
7440-50-8
RTECS #:GL5325000
Fraction by Wt: 10-30%
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2MG/M3 FUME; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CARBON BLACK */FULLY BAKED OUT
CAS:1333-86-4
RTECS #:FF5800000
OSHA PEL:3.5 MG/M3 *
ACGIH TLV:3.5 MG/M3; 9192 *

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXPOSURE T

O FUMES MAY CAUSE
BRONCHITIS,LUNG DEPOSITS AND TISSUE DAMAGE WHICH MAY BE
IRREVERSIBLE. EXPOSURE TO ULTRA- VIOLET ARC RAYS CAN RESULT IN
KERATOCONJUNCTIVITIS,CAUSING INFLAMMATION, BLURRED VI
SION,HEADACHE-"SUNBURN".

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:BREATHING DIFFICULTY,HEADACHE,NAUSEA,DRYNESS OR
IRRITATION OF NOSE,THROAT AND EYES. BURNING SENSATION OF SKIN OR
EY
ES. UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF
RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:FOR INHALATION EXPOSURE, REMOVE TO FRESH AIR. IF BREATHING
IMPAIRED, ASSISTED RESPIRATION MAY BE REQUIRED. TREAT U. V. SIMILAR
TO SEVERE SUNBURN, SEEK MEDIAL ATTENTION!

===== Fire Fighting Measures =====

Flash Point:NOT FLAMMA
BLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:NONFLAMMABLE. USE MEDIA AS APPROPIATE FOR
SURROUNDING FIRE.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-
APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE
OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP OR PICK UP. BE ALERT TO "
HOT ENDS".

Neutralizing Agent:NONE APPLICABLE FOR THIS MATERIAL

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY AREA. ELECTRODES EXPOSED
TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING
AT 300F FOR TEN HOURS.

Other Precautions:READ AND UNDERSTAND "AMERICAN NATIONAL STANDARD
Z49.1"; SUBPART Q OF OSHA 29 CFR 1910.252; "SAFETY IN WELDING AND
CUTTING" BY THE AMERICAN WELDING SOCIETY.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection: AIR SUPPLIED OR FUME RESPIRATOR MUST BE USED IF VENTILATION IS INSUFFICIENT.

Ventilation: LOCAL EXHAUST VENTILATION TO KEEP EXPOSURE BELOW TLV.

Protective Gloves: WELDER'S GLOVES

Eye Protection: WELDER'S HELMET WITH # 12 OR DARKER LENS

Other Protective Equipment: DARK, SUBSTANTIAL APRONS, FOOTWEAR SUITABLE FOR METAL WORKING.

Work Hygienic Practices: FOLLOW STANDARD HYGIENE PRACTICES OF YOUR LOCAL SHOP.

Supplemen

tal Safety and Health

TRAIN OPERATOR TO AVOID ELECTRICAL SHOCK AND EXPOSURE TO U.V. RAYS.

SAMPLE AIR TO DETERMINE EXPOSURE CONCENTRATIONS AND TO TAKE CORRECTIVE ACTION.

===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: NOT GIVEN

Melt/Freeze Pt: M.P/F.P Text: NOT GIVEN

Vapor Pres: NOT GIVEN

Vapor Density: NOT GIVEN

Spec Gravity: NOT GIVEN

Evaporation Rate & Reference: NIL

Solubility in Water: INSOLUBLE

Appearance and Odor: COPPER COATED BLACK R
OD. NO NOTABLE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE,
TRACES OF COPPER FUME (OZONE, NITROGEN OXIDE FROM THE ELECTRIC ARC
AND UV RAYS).

===== Disposal Considerations =====

Waste Disposal Methods: CONTACT YOUR LOCAL ENVIRO

NMENTAL OFFICER.

DISPOSE OF AT SOLID LANDFILL IF REGULATIONS ALLOW. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.