

SEAGUARD CORP. -- FORMULA 105 RED ANTI-FOULING -- 8010-00-290-6651

=====
Product Identification
=====

Product ID:FORMULA 105 RED ANTI-FOULING

MSDS Date:01/01/1987

FSC:8010

NIIN:00-290-6651

MSDS Number: BDVHJ

=== Responsible Party ===

Company Name:SEAGUARD CORP.

Emergency Phone Num:804-4884411

CAGE:JO928

=== Contractor Identification ===

Company Name:MILITARY SPECIFICATIONS PROMULGATED BY MILITARY

Address:DEPTS/AGENCIES UNDER AUTH OF DEF STD

Box:MANUAL

City:4120 3-M

Phone:804-279-4371 DSN 695-4371

CAGE:81349

Company Name:SEAGUARD CORP.

CAGE:JO928

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 17%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effec

ts of Overexposure:MAYBE IRRITATING TO SKIN AND UPPER RESPIRATORY SYSTEM

=====
First Aid Measures
=====

First Aid:WASH EXPOSED AREAS FREELY WITH WATER.REMOVE SUBJECT TO WELL VENTILATED AREA.CALL PHYSICIAN IF NECESSARY.

=====
Fire Fighting Measures
=====

Flash Point:81F,27C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,ALCOHOL FOAM

Unusual Fire/Explosion Hazard:VAPORS FLASH BACK

A CONSIDERABLE DISTANCE
TO ORIGIN

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL DRY PLACE FREE FROM OPEN
FLAMES AND PHYSICAL ABUSE WITH GOOD VENTILATION
Other Precautions:ODOR THRESHOLD IS NOT ADEQUATE TO WARN OF POTENTIALLY
DANGEROUS CONCENTRATIONS.SECURE ALL SOURCES OF IGNITION.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPROVED FULL-FACE ORGANIC RESPIRAT
OR
Ventilation:LOCAL EXHAUST FOR ENCLOSED OPERATIONS
Protective Gloves:YES
Eye Protection:YES
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F3
Boiling Pt:B.P. Text:241F,116C
Vapor Pres:10
Vapor Density:3.66
Spec Gravity:1.72
Evaporation Rate & Reference:1
Solubility in Water:SLIGHT
Appearance and Odor:THICK RED LIQUID WITH NORMAL PETROLEUM ODOR
Percent Volatiles by Volume:28

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
WATER AND AQEOUS SOLUTIONS
Stability Condition to Avoid:OPEN FLAME AND UNGROUNDED EQUIPMENT

=====
Disposal Considerations
=====

Waste Disposal Methods:REFER TO RESOURCE CONSERVATION AND RECOVERY
ACT,PL584-2024.DIRECT ASSISTANCE AVAILABLE FROM SOLID WASTE
MANAGEMENT DIVISION,USAEHA,AV 584-2024

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for

use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.