

PHOENIX PLASTICS INC -- O-L-298B -- 6850-00-291-0963

===== Product Identification =====

Product ID:O-L-298B

MSDS Date:01/01/1985

FSC:6850

NIIN:00-291-0963

MSDS Number: BDVKS

=== Responsible Party ===

Company Name:PHOENIX PLASTICS INC

Address:215 S 23RD ST

City:PHOENIX

State:AZ

ZIP:85034-2503

Country:US

Emergency Phone Num:617-542-7341

CAGE:06372

=== Contractor Identification ===

Company Name:PHIPP

S PRODUCTS CORP

Address:186 LINCOLN ST SUITE 502

Box:City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Phone:OUT OF BUSINESS

CAGE:86511

Company Name:PHOENIX PLASTICS INC

Address:215 S 23RD ST

Box:City:PHOENIX

State:AZ

ZIP:85034-2503

Country:US

CAGE:06372

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENTS

Fraction by Wt: 1000%

ACGIH TLV:300 PPM

===== Hazards Identification =====

Effects of Overexposure:SEVERE EYE IRRITANT,

DRYING SKIN. XS
INHALE=HEADACHE, DIZZINESS & NAUSEA.

===== First Aid Measures =====

First Aid:EYE:FLUSH W WATER. SKIN:WASH W MILD SOAP & WATER & APPLY SKIN CREAM. INHALATION:REMOVE TO FRESH AIR & CALL PHYSICIAN;APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point:102F, 39C TCC
Lower Limits:0.7
Upper Limits:6.0
Fire Fighting Procedures:WATER SPRAY, CO2, FOAM, DRY CHEM

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH W WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE OR HOT METAL SURFACES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPSRKS & OPEN FLAME. USE W ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory
Protection:SELF-ONT BREATH APPARAT IF TLV EXCEEDED.
Ventilation:LOCAL
Protective Gloves:YES
Eye Protection:YES
Other Protective Equipment:EYE BATH & SAFETY SHOWER
Supplemental Safety and Health
BP:157-193C

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315-380
Vapor Pres:2
Vapor Density:4.9
Spec Gravity:0.766
Evaporation Rate & Reference:0.06/TOLUENE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WATER-WHITE
Percent Volatiles by Volume

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid: HEAT; SPARKS, OPEN FLAME & FIRE.
Hazardous Decomposition Products: CO

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF
IN ACCORD W LOCAL, STATE OR FED REG.

Disclaimer (provided with this information by the compiling agencies):
This

information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.