View NSN Online: https://aerobasegroup.de/nsn/6830-00-292-0147

DU PONT E I DE NEMOURS AND CO INC -- FREON 12 FLUOROCARBON -- 6830-00-292-0147

Product ID:FREON 12 FLUOROCARBON

MSDS Date:05/01/1989

FSC:6830

NIIN:00-292-0147

MSDS Number: BDVPD === Responsible Party ===

Company Name: DU PONT E I DE NEMOURS AND CO INC

Address:1007 MARKET STREET

Box:1635

City:WILMINGTON

State:DE ZIP:19899 Country:US

Info Phone Num:800-441-9450

Emer

gency Phone Num:800-441-3637 Preparer's Name:K.P. BROWN

CAGE:18873

=== Contractor Identification ===

Company Name: E.I. DUPONT DE NEMOURS & CO

Address:1007 MARKET STREET

Box:City:WILMINGTON

State:DE ZIP:19898 Country:US

Phone:800-441-7515;800-441-9442

CAGE:18873

======= Composition/Information on Ingredients ========

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000 Fraction by Wt: 100% OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT

Rpt Qty:5000 LBS Ozone Depleting Chemical:1
======================================
LD50 LC50 Mixture:LC 50 RAT 800,000 PPM/30 MIN Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION OF HIGH CONCENTRATIONS OF VAPOR IS HARMFUL AND MAY CAUSE HEART IRREGULARITIES, UNCONSCIOUSNESS, OR DEATH. INTENTIONAL MISUSE CAN BE FATAL. LIQUID CONTACT CAN CAUSE FROSBITE . MAY CAUSE EYE I RRITATION. Explanation of Carcinogenicity:DATA PER MSDS Effects of Overexposure:EYE IRRITATION WITH DISCOMFORT, TEARING, OR BLURRING OF VISION. SKIN CONTACT MAY RESULT IN FROSTBITE. INHALING
MAY CAUSE TEMPORARY NERVOUS SYSTEM DEPRESSION WITH DIZZINESS, HEADACHE, CONFUSION, INCOOR DINATION, AND LOSS OF CONSCIOUSNESS. EXCESSIVE EXPOSURES MAY CAUSE HEART AND CIRCULATORY IRREGULARITIES. Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PREEXISTING DISEASES OF THE CENTRAL NERVOUS OR CARDIOVASCULAR SYSTEM MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.
First Aid:EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.SEE DOCTOR. SKIN:FLUSH WITH WATER.TREAT FOR FROSTBITE IF NECESSARY. INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXIGEN IF NEEDED.SEE DOC TOR. INGESTION:SEE DOCTOR. NOTE TO PHYSICIAN:BECAUSE OF POSSIBLE CARDIAC DIST URBANCE, CATECHOLAMINE DRUGS, SUCH AS EPINEPHRINE SHOULD BE USED WITH SPECIAL CAUTION.

Flash Point:NONE

Extinguishing Media: AS APPROPRIATE FOR COMBUSTIBLES IN AREA.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:USE WATER SPRAY OR FOG TO COOL C

DECOMPOSITION MAY OCCUR.
========== Accidental Release Measures ==========
Spill Release Procedures: VENTILATE AREA, ESPECIALLY LOW PLACES WHERE HEAVY VAPORS MIGHT COLLECT. REMOVE OPEN FLAMES. USE SCBA FOR LARGE SPILLS.
Neutralizing Agent:NONE APPLICABLE FOR THIS MATERIAL
=========== Handling and Storage ==============
Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE, HEAT AND IGNITION SOURCES. KEEP CONTAINERS CLOSED. DO NOT STORE ABOVE 125F. Other Precautions:AVOID BREATHING VAPORS AND LIQUID CONTACT WITH SKIN OR EYES. USE ONLY IN WELL VENTILATED AREA.
===== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE REQUIRED FOR ADEQUATELY VENTED WORK SITUATIONS. FOR ACCIDENTAL OR NON-VENTILATED SITUATIONS, USE A SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR RESPIRAT OR,
APPROVED BY NIOSH. Ventilation:MECHANICAL (GENERAL) VENTILATION IS REQUIRED. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA IS NOT VENTED. Protective Gloves:BUTYL RUBBER, PVA OR NEOPRENE Eye Protection:CHEMICAL SPLASH GOGGLES Other Protective Equipment:USE IMPERVIOUS CLOTHING IF THERE IS REPEATED OR PROLONGED CONTACT WITH LIQUID. Work Hygienic Practices:STANDARD HYGENIC PRACTICES. Supplemental Safety and Health NONE.
======================================
HCC:G3 Boiling Pt:B.P. Text:-21.6F/-29C Vapor Pres:94.5 Vapor Density:4.26 Spec Gravity:1.315 pH:NEUTR. Solubility in Water:0.028 Appearance and Odor:CLEAR,COLORLESS LIQUEFIED GAS,SLIGHT ETHEREAL ODOR Percent Volatiles by Volume:100
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES ALKALI OR ALKALINE EARTH METALS-POWDERED AL, ZN, BE, ETC. Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAMES Hazardous Decomposition Produ

ONTAINERS. CYLINDERS MAY RUPTURE UNDER FIRE CONDITIONS.

cts:HYDROCHLORIC AND HYDROFLUORIC
ACIDS-POSSIBLY CARBONYL HALIDES. DECOMPOSED BY HIGH
TEMPERATURES(OPEN FLAMES, HOT METAL)

======= Disposal Considerations ===========

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.
RECLAIM BY DISTILLATION OR REMOVE TO A PERMITTED FACILITY. DISPOSE
OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This i

nformation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.