View NSN Online: https://aerobasegroup.de/nsn/8010-00-297-0556

## 

Product ID:741610 ENAMEL ALKYD LUSTREL

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0556

MSDS Number: BDVYM
=== Responsible Party ===
Company Name:PRAXAIR INC
Address:39 OLD RIDGEBURY RD

City: DANBURY

State:CT

ZIP:06817-0001 Country:US

Info Phone Num:203-794-5782

Emergency Phone Num:203-794-5782

CAGE:0LV0

1

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name: PRAXAIR, INC. Address: 39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06810-5113

Country:US

Phone:800-772-9247; 800-PRAXAIR

CAGE:0LV01

====== Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS

CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 35% ACGIH TLV:500 PPM

\_\_\_\_\_

== Hazards identification =============
Effects of Overexposure:INHALATION-ANESTHETIC,IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.
======================================
First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.
======================================
Flash Point:104F, 40C TCC
Lower Limits:1.10 Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED
========= Accidental Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS VENTILATE AREA REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106 Other Precautions:GROUND CONTAINERS WHEN POORING AVOID FREE FALL OF LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPIATE VENTILATION.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:OPEN AREA B

UR MINES MECH RESPIRATOR-CLOSED-BUR MINES CHEM/MECH FILTE Ventilation: GENERAL DILUTION OR LOCAL EXHAUST TO KEEP TLV BELOW LIMIT. Protective Gloves: REG IF LONG CON Eye Protection: TO PROTECT VS SPLASHING Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING. Supplemental Safety and Health ======== Physical/Chemical Properties =============== HCC:F4 Boiling Pt:B.P. Text:311-373F Vapor Density:>AIR Evaporation Rate & Description Rate & Reference: SLOWER THAN ETH ER Percent Volatiles by Volume:57 ======== Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES

======= Disposal Considerations ============

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elem ents of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.