

PRATT & LAMBERT - WICHITA DIV. -- 741-204+TT-E-527C COMP L; 32246 ORANGE --  
8010-00-297-0563

=====  
Product Identification  
=====

Product ID:741-204+TT-E-527C COMP L; 32246 ORANGE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0563

MSDS Number: BDVYY

=== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIV.

Emergency Phone Num:(316) 733-1361

CAGE:PRATT

=== Contractor Identification ===

Compa

ny Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR  
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:MO

LYBDATE ORANGE (5-10%)

CAS:12656-85-8

RTECS #:QA4660000

ACGIH TLV:0.05 MG/CUM

Ingred Name:MAGNESIUM SILICATE

Ingred Name:DIATOMACEOUS SILICA

=====  
Hazards Identification  
=====

Effects of Overexposure:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE  
CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE: IRRIT

=====  
First Aid Measures  
=====

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE  
REMOVING CO  
NTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR.  
CALL A PHYSICIAN IF SYMPTOMS PERSIST.

=====  
Fire Fighting Measures  
=====

Flash Point:104F TCC

Lower Limits:1.1

Extinguishing Media:SM FIRES: CO\*2, DRY CHEM. LG FIRES: POLYMER FOAM  
PREFERRED

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD-UP.

=====  
Accidental Release Me  
asures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT  
SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID  
BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT &  
NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LG QTY  
IN BUILDINGS DESIGNED TO COMPLY W/OSHA 1910.106 DO NOT TAKE  
INTERNALLY. ADD LABEL WARNING.

Other Prec

autions:GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQ IN EXCESS OF FEW IN. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DOT: COMBUSTIBLE

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESTRICT VEN: CHEM-MECH FLTR.  
CLSD: AIR-LINE TYPE

Ventilation:GEN DILTN/LOCAL EXHST TO KEEP LV/LEL BELOW LIMIT, REMV FUME

Protective Gloves:YES

Eye Protection:YES, FOR SPLA

SH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

ADDRESS:630 EAST 13TH,ANDOVER,KS 67002.THIS PRODUCT IS A LUSTERLESS ENAMEL ALKYD.VAPOR PRESSURE BASED ON MINERAL SPIRITS IS 3.2.VAPOR DENSITY:HEAVIER THAN AIR.WT PER GAL:10.6 LBS.

=====  
===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference:SLOWR THAN ETHER

Percent Volatiles by Volume:58.

=====  
===== St  
ability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/FED., STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.