

PRAXAIR INC -- 745314 ENAMEL ALKYD SG YELLOW 23594 -- 8010-00-297-0583

===== Product Identification =====

Product ID:745314 ENAMEL ALKYD SG YELLOW 23594

MSDS Date:01/01/1987

FSC:8010

NIIN:00-297-0583

MSDS Number: BDVZQ

=== Responsible Party ===

Company Name:PRAXAIR INC

Address:39 OLD RIDGEBURY RD

Box:2153

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:203-794-5782

Emergency Phone N

um:203-794-5782

CAGE:0LV01

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

Company Name:PRAXAIR, INC.

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06810-5113

Country:US

Phone:800-772-9247; 800-PRAXAIR

CAGE:0LV01

===== Composition/Information on Ingredients =====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3

)
CAS:7758-97-6
RTECS #:GB2975000
OSHA PEL:0.05 MG/M3 (PB)
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:XYLENES (O-,M-,P
- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:LOSS OF APPETITE METALLIC TASTE IN MOUTH
ANXIETY DAMAGE TO NERVOUS URINARY & REPRODUCTIVE SYSTEMS

===== First Aid Measures =====

First Aid:IF SWALLOWED INDUCE VOMITING CONSULT POISON CONTROL
CENTER.INHALA

TION-REMOVE TO FRESH AIR GIVE ARTIFICIAL RESPIRATION
IF REQUIRED.EYE-FLUSH WITH LARGE AMOUNTS OF WATER FOR 15
MINUTES.SKIN-WASH AFFECTE D AREA WITH SOAP-WATER.

===== Fire Fighting Measures =====

Flash Point:80F (26.7C)
Extinguishing Media:CLASS B
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE AT HIGH
HEAT

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITION
SOURCES. DIKE AND CONTAIN SPILL WITH INERT MATERIAL. TRANSFER
LIQUIDS TO COVERED METAL CONTAINERS. PREVENT CONTAMINATION OF SEWER
STREAMS & GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106
Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH

USE. DO NOT BREATHE SANDING DUST. EMPTY CONTAINERS MUST NOT BE
WASHED OR REUSED FOR ANY PURPOSE. NEVER USE PRESSURE TO EMPTY

===== Exposure Controls/Personal Protection =====

Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION
Protective Gloves:SOLVENT INPERME
Eye Protection:SAFETY GLASSES W/SHIELD
Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT
Supplemental Safety and Health

===== Physical/Chemical Properties =====
=====

HCC:F3
Boiling Pt:B.P. Text:244F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:56

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS
Stability Condition to Avoid:NONE KNOWN
Hazardous Decomposition Products:BURNING CAUSES CARBON MONOXIDE &
DIOXIDE - OXIDES OF LEAD

===== Disposal Considerations =====

Waste Di

Disposal Methods: DISPOSE IN ACCORDANCE WITH FEDERAL STATE & LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.