

ATLAS PAINT & VARNISH CO -- TT-E-529C, OLIVE DRAB PAINT 24087 -- 8010-00-297-0586

=====  
Product Identification  
=====

Product ID:TT-E-529C, OLIVE DRAB PAINT 24087

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0586

MSDS Number: BDWBK

=== Responsible Party ===

Company Name:ATLAS PAINT & VARNISH CO

Emergency Phone Num:201-373-3300

CAGE:KO008

=== Contractor Identification ===

Company Name:ATLAS PAINT & VA

RNISH CO.

CAGE:KO008

Company Name:ATLAS PAINT AND VARNISH CO

CAGE:84239

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PIGMENTS (SEE SUPPLIMENTAL DATA FOR SPECIFIC TYPES)

Fraction by Wt: 30.0%

ACGIH TLV:15 MG/CUM-MFG

Ingred Name:ALKYD RESIN

Fraction by Wt: 27.0%

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 41.0%

OSHA PEL:100 PPM

Ingred Name:LEAD COBALT DRIERS (OSHA PEL FROM 29CFR 1910.1025)

Fraction by Wt

: 1.0%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALATION: (HIGH CONC) MAY CAUSE MILD  
DEPRESSION & LOSS OF CONSCIOUSNESS

=====  
First Aid Measures  
=====

First Aid:REMOVE FROM EXPOSURE & CALL PHYSICIAN. FLUSH AFFECTED PARTS  
WITH WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:108F TCC

Lower Limits:0.

09

Upper Limits:6.0

Extinguishing Media:CO\*2, FOAM, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:USE AIR-SUPPLIED RESCUE EQUIP - COOL EXPOSED CONTAINER.

Unusual Fire/Explosion Hazard:USUAL HAZARD POTENTIAL BASED ON FLASH POINT

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IMMEDIATELY & DISCARD ABSORBENTS SAFELY. REMOVE OPEN IGNITION. DIKE LG SPILLS & PUMP INTO WASTE TANK. KEEP VENTILATED & AVOID PROLONGED BREATHING OF VAPORS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID OPEN FLAMES - SPARKS & EXCESSIVE HEAT - VENTILATE AREA

Other Precautions:READ LABEL REGARDING TOXICITY & APPLICATION. DOT: COMBUSTIBLE LIQUID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED - NIOSH APPROVED RESP PROT FOR PART EXP OF CONCERN

Ventilation:LOCAL EXHAUST: MOST DESIRABLE

Protective Gloves:RECOMMENDED

E

Eye Protection:RECOMMENDED

Other Protective Equipment:CONVENTIONAL CLOTHING FOR PAINTING

Supplemental Safety and Health

PIGMENTS: MED CHROME YELLOW, CARBON BLACK, RED OXIDE, SILICATE, BARYTES. MFG SUGGESTS TLV OF 200 PPM PER 8 HR WORK DAY. VAPOR PRESSURE IS