

PRATT & LAMBERT COMPANY, WICHITA DIVISION -- 723-438 PRIMER COATING,ZN CHROMATE  
COLOR Y -- 8010-00-297-0593

=====  
Product Identification  
=====

Product ID:723-438 PRIMER COATING,ZN CHROMATE COLOR Y

MSDS Date:01/01/1987

FSC:8010

NIIN:00-297-0593

MSDS Number: BDWCB

=== Responsible Party ===

Company Name:PRATT & LAMBERT COMPANY, WICHITA DIVISION

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

CAGE:PRATT

=== Contractor Identification ===

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0

.01MG/M3(CR)A1;9192

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000

Fraction by Wt: < 5%

OSHA PEL:S,200 PPM

ACGIH TLV:S, 5 PPM; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ACETATE

RTECS #:AL4025000

Fraction by Wt: < 5%

ACGIH TLV:150 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: < 5%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL

(SARA III)

CAS:78-83-1

RTECS #:NP9625000

Fraction by Wt: < 5%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:INHAL CAUSE ANESTHETIC, IRRIT OF RESP TRACT,  
ACUTE NERVOUS SYSTEM DEPRESSION. SEE OTHER PRECAUTIONS.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH WATER.  
REMOVE CO

NTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

=====  
Fire Fighting Measures =====

Flash Point:13F;-10.6C (TCC)

Lower Limits:0.9

Extinguishing Media:CO\*2,DRY CHEM,ALCOHOL FOAM,H\*2O SPRAY INEFFECTIVE  
-SUPP DATA

Fire Fighting Procedures:USE SCBA;USE H\*2O TO COOL HEAT-EXPOSED CANS

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. AVOID SOURCES OF IGNITION-POSS PRESSURE BUILD UP,AUTO-IGNITION

=====  
Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES, HOT SURFACES & ELECTRICAL, STATIC OR FRICTIONAL SPARKS. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS.

=====  
Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE > 120F; 49C. STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106. DO NOT FLAME CUT,BRAZ  
E,WELD WITHOUT RESP PROTECT.

Other Precautions:EFFECTS OVEREXPOS: DEPRESSION CHARACTERIZED BY HDCH, DIZZ, STAG GAIT, CONFUSION, UNCON OR COMA. PRODUCT CAUSES SKIN & EYE IRRITATION. GROUND CONTAINER WHEN POURING,AVOID FREE FALL > FEW INCHES

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOORS: NIOSH/MSHA APPRVD MECH FILTER RESP. SEE OTHER EQUIP.

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST TO KEEP < TLV.

Protective Gloves:RECOMMEND  
ED

Eye Protection:SPLASH PROOF

Other Protective Equipment:USE NIOSH/MSHA APPRVD AIR LINE RESP IN CONFINED AREAS.

Supplemental Safety and Health

INGRED: ALIPHATIC NAPHTHA II-5-10%,TLV=200PPM(MFR);ALIPHATIC NAPHTHA-