View NSN Online: https://aerobasegroup.de/nsn/8010-00-297-0802

## AMERON PROTECTIVE COATIONS -- GREY 36231 -- 8010-00-297-0802

============ Product Identification ==============

Product ID:GREY 36231 MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0802

MSDS Number: BDWCP === Responsible Party ===

Company Name: AMERON PROTECTIVE COATIONS

Address: 201 N BERRY STREET

City:BREA State:CA ZIP:92621 Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4 === Contrac

tor Identification ===

Company Name: AMERON PROTECTIVE COATINGS

Address: 201 NORTH BERRY STREET

Box:1020 City:BREA State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL BENZENE \*98-2\*

CAS:100-41-4

RTECS #:DA0700000
Fraction by Wt: LT5%
Other REC Limits:100 PPM
OSHA PEL:435 MG/CUM
ACGIH TLV:434 MG/CUM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name: ISOBUTYL ACETATE

CAS:110-19-0 RTECS #:AI4025 000 Fraction by Wt: LT5% Other REC Limits: 150 PPM OSHA PEL:150 PPM ACGIH TLV:713 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000 Fraction by Wt: 22.0%

Other REC Limits: STEL 400 PPM

OSHA PEL:100 PPM ACGIH TLV:300 PPM

Ingred Name: ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL

CAS:78-83-1

RTECS #:NP9625000 Fraction by Wt: 10.0% Other REC Limits:50 PPM OSHA PEL:300 MG/CUM ACGIH TLV:152 MG/CUM

EPA Rp

t Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

**Explanation of Carcinogenicity:NONE** 

Effects of Overexposure: ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE

NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

First Aid: IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE

CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST.

Flash Point Method:TCC

Flash Point:50F Lower Limits:0.9

Extinguishing Media: SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE FIRES-FOAM

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT MAY **EXPLODE** 

====== Acci

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INET ABSORBENT NON-SPARKING TOOLS
======================================
Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY Supplemental Safety and Health
RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE
========= Physical/Chemical Properties =========
HCC:F2 Boiling Pt:B.P. Text:223-290F Evaporation Rate & Dercen t Volatiles by Volume:60.0
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES
======= Disposal Considerations ==========
Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS
Disclaimer (provided with this information by the compiling agencies): This information is formula

dental Release Measures =========

ted for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.